

Ring terminals

Nylon-insulated ring terminals

Note: Sta-Kon rings, forks and locking forks are tested and listed to UL 486A/B, two-way splices to UL 486C, disconnects to UL 310 and all applicable products to CSA 22.2.

Sta-Kon® rings, forks and locking forks

- Complete line of installing tools engineered to match tool with terminal
- First to gain military approval for pressure connections many styles available for military applications
- Sta-Kon products exceed test specification requirements of military, UL® and CSA



- Include extra metal sleeve to grip insulation
- Vinyl insulated and bare Sta-Kon terminals feature brazed seam wire barrels that can be crimped at any place on the barrel circumference
- Can be installed with crimping tools having a single indentor or double indentor (recommended for solid wire)
- Serrated barrel increases grip on wire
- Wire range identification on the tongue of each terminal
- Can be installed with crimping tools having a single indentor or double indentor (recommended for solid wire)
- Constructed of electrolytic copper for high conductivity
- Wire range identification on the tongue of each terminal

Nylon-insulated ring terminals




Cat. no.	Pkg. qty.	Wire range (AWG)	Max. ins. (in.)	Bolt hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)
						A	B	C	M	
RZ22-2**	100	26-22	0.083	#2	ERG4006	0.57	0.14	0.13	0.49	0.02
RZ22-4**	100	26-22	0.083	#4		0.65	0.21	0.20	0.54	
RZ22-6**	100	26-22	0.083	#6		0.65	0.21	0.20	0.54	
RZ22-8**	100	26-22	0.083	#8		0.75	0.25	0.23	0.62	
RZ22-10**	100	26-22	0.083	#10		0.75	0.25	0.23	0.62	
RAX23*	1,000	26-24	0.125	#2	WT145A	0.66	0.14	0.14	0.59	0.02
RAX43*	1,000	26-24	0.125	#4		0.74	0.20	0.19	0.64	
RAX63*	1,000	26-24	0.125	#6		0.84	0.25	0.22	0.72	
RAX83*	1,000	26-24	0.125	#8		0.84	0.25	0.22	0.72	
RAX103*	1,000	26-24	0.125	#10		0.84	0.25	0.24	0.72	
RA18-4	100	22-16	0.136	#4	ERG4001	0.72	0.23	0.14	0.59	0.03
RA323	1,000	22-16	0.136	#4		0.72	0.23	0.14	0.59	
RA333	1,000	22-16	0.136	#6		0.72	0.23	0.14	0.59	
RA18-6	100	22-16	0.136	#6		0.86	0.26	0.25	0.71	

* Not listed by UL or CSA

** CSA listed only

Cat. no.	Pkg. qty.	Wire range (AWG)	Max. ins. (in.)	Bolt hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)
						A	B	C	M	
RA853	1,000	22-16	0.136	#6	WT145A	0.86	0.26	0.25	0.71	0.03
RA18-8	100	22-16	0.136	#8		0.89	0.26	0.25	0.71	
RA833	1,000	22-16	0.136	#8		0.86	0.26	0.25	0.71	
RA863	1,000	22-16	0.136	#8		0.89	0.26	0.25	0.71	
RA18-10	100	22-16	0.136	#10		0.89	0.31	0.25	0.71	
RA873	1,000	22-16	0.136	#10		0.89	0.31	0.25	0.71	
RA18-14	100	22-16	0.136	¾		1.10	0.46	0.31	0.84	
RA713	1,000	22-16	0.136	¾		1.10	0.46	0.31	0.84	
RA18-516	100	22-16	0.136	5/16		1.10	0.46	0.31	0.84	
RA723	1,000	22-16	0.136	5/16	ERG4001	1.10	0.46	0.31	0.84	0.03
RA18-38	100	22-16	0.136	¾		1.20	0.53	0.35	0.87	
RA733	1,000	22-16	0.136	¾		1.20	0.53	0.35	0.87	
RA18-12	100	22-16	0.136	½		1.30	0.72	0.50	0.92	
RA753	1,000	22-16	0.136	½		1.30	0.72	0.50	0.92	

Diagram





Ring terminals

Non-insulated large ring terminals – Brazed seam



Non-insulated large ring terminals – Brazed seam



Cat. no.	Pkg. qty.	Wire range (AWG)	Bolt hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)
					A	B	C	M	
D8-10	25	8	#10	TBM6S	1.09	0.42	0.34	0.90	0.06
D36	200	8	#10		1.09	0.42	0.34	0.90	
D26	200	8	#10		1.13	0.48	0.36	0.90	
D8-14-SK	25	8	1/4		1.13	0.48	0.36	0.90	
D71	200	8	1/4		1.13	0.48	0.36	0.90	
D8-516	25	8	5/16		1.32	0.59	0.49	1.03	
D72	200	8	5/16		1.32	0.59	0.49	1.03	
D8-38	25	8	3/8		1.32	0.59	0.49	1.03	
D73	200	8	3/8		1.32	0.59	0.49	1.03	
D8-12	25	8	1/2		1.49	0.82	0.55	1.09	
D75	200	8	1/2		1.49	0.82	0.55	1.09	0.06
E6-10	20	6	#10		1.13	0.48	0.36	0.90	
E26	200	6	#10		1.13	0.48	0.36	0.90	
E6-14	20	6	1/4		1.13	0.48	0.36	0.90	
E71	200	6	1/4		1.13	0.48	0.36	0.90	
E6-516	20	6	5/16		1.32	0.60	0.49	1.03	

Cat. no.	Pkg. qty.	Wire range (AWG)	Bolt hole (in.)	Rec. tool	Dimensions (in.)				Stock thick. (in.)
					A	B	C	M	
E72	200	6	5/16	TBM6S	1.32	0.60	0.49	1.03	0.06
E6-38	20	6	3/8		1.32	0.60	0.49	1.03	
E73	200	6	3/8		1.32	0.60	0.49	1.03	
E6-12	20	6	1/2		1.49	0.82	0.55	1.08	
E75	200	6	1/2		1.49	0.82	0.55	1.08	
F4-10	20	4	#10		1.16	0.48	0.36	0.93	0.07
F26	200	4	#10		1.16	0.48	0.36	0.93	
F4-14	20	4	1/4		1.16	0.48	0.36	0.93	
F71-TB	200	4	1/4		1.16	0.48	0.36	0.93	
F4-516	20	4	5/16		1.35	0.60	0.49	1.06	
F72	200	4	5/16		1.35	0.60	0.49	1.06	
F4-38	20	4	3/8		1.35	0.60	0.49	1.06	
F73	200	4	3/8		1.35	0.60	0.49	1.06	
F4-12	20	4	1/2		1.52	0.82	0.55	1.11	
F75	200	4	1/2		1.52	0.82	0.55	1.11	

