


Pipe Straps, Conduit Clamps and Hangers

Pipe Clamps — A-726, Alloy Three-Bolt Pipe Clamp

Designed for hot-insulated pipelines. The spacer on the top inner bolt provides uniform space for the connecting eyerod or weldless eyenut.

Temperature range: above 750° F (399° C) to 1050° F (566° C).

- Specifications**
- Material: Chromium Molybdenum Steel, ASTM A-387 Grade 22
 - Compliance: Federal Specification A-A-1192A Type 3, MSS-SP-69 Type 3 and BSPSS-BS3974
 - Finish: Standard Finish — GoldGalv®, Black (add suffix "-B"), Electro-Galvanized (add suffix "-EG")
 - Ordering: Specify catalog number and pipe size



CAT. NO.	PIPE SIZE (IN.)	MAXIMUM LOAD			B (IN.)	C (IN.)	D (IN.)	TAKE OUT E (IN.)	F (IN.)	H (IN.)	(LBS.)
		950° F/510° C	1000° F/538° C	1050° F/566° C							
A-726-3/4	¾	870	600	440	1½	¾	3	2½	¾	1½	1.09
A-726-1	1	870	600	440	1½	¾	3½	2¾	¾	1¾	1.14
A-726-1-1/4	1¼	870	600	440	1½	¾	3¾	2¾	¾	2¼	1.23
A-726-1-1/2	1½	1,400	1,000	700	1¾	1	4½	4¼	¾	2½	2.48
A-726-2	2	1,400	1,000	700	2½	1	5½	5¼	¾	2¾	2.70
A-726-2-1/2	2½	1,400	1,000	700	2½	1	6½	5¾	¾	3	2.76
A-726-3	3	1,400	1,000	700	2¾	1	6¾	6	¾	3½	3.19
A-726-4	4	2,300	1,600	1,100	3¾	1	7¾	6½	¾	4½	7.30
A-726-5	5	2,300	1,600	1,100	4	1½	8½	7	¾	5½	7.96
A-726-6	6	2,600	1,800	1,300	4¾	1½	10	8½	¾	6½	12.26
A-726-8	8	2,600	1,800	1,300	5¾	1½	11	9¾	¾	7½	14.04
A-726-10	10	3,000	2,100	1,500	6¾	1¾	12	10½	1	8¼	21.33
A-726-12	12	3,000	2,100	1,500	8¾	1½	13¾	11¾	1	9¾	24.00
A-726-14	14	3,900	2,800	2,000	9¾	2	14¾	12¾	1¼	10¾	38.78
A-726-16	16	3,900	2,800	2,000	10	2	15½	14	1¼	11¾	43.13
A-726-18	18	39	2,800	2,000	11¾	2	16¾	15½	1¼	13¾	47.78
A-726-20	20	5,000	3,200	2,000	12¾	2	17½	15¾	1½	14	58.67
A-726-24	24	5,500	3,500	2,700	14¾	1½	19¾	17¾	1½	16¾	90.82


Standard Finish — GoldGalv®, unless otherwise stated.

Pipe Hangers — C-710, C-710F, C-710P, C-710SS

Designed to support non-insulated, stationary lines from above, allowing for approximately 1" to 1½" of vertical adjustment after the pipe is in place. The lower nut (not furnished) adjusts the pipe line to the proper elevation, the top nut (not furnished) prevents loosening due to vibration and must be tightened securely to assure proper hanger performance.

Rated Loads are for up to 650° F (343° C) for carbon steel. Maximum PVC temperature is 140° F (60° C).

- Specifications**
- Material: Carbon Steel (Also available in Stainless Steel as C-710SS)
 - Compliance: Federal Specification A-A-1192A Type 1, MSS-SP-69 Type 1, BSPSS-BS3974, UL and FM
 - Finish: Standard Finish — GoldGalv®, Black (add suffix "-B"), Electro-Galvanized (add suffix "-EG")
 - Ordering: Specify catalog number, finish and pipe size



CAT. NO.	PIPE SIZE (IN.)	MAX. LOAD (LBS.)	A (IN.)	B (IN.)	C (IN.)	ROD TAKE OUT E (IN.)	WT. EACH (LBS.)
C-710-1/2	½	610	¾	2¾	3¾	1½	.27
C-710-3/4	¾	610	¾	2½	2¾	1½	.29
C-710-1	1	610	¾	3	3¾	2¼	.33
C-710-1-1/4	1¼	610	¾	3¾	4	2¼	.36
C-710-1-1/2	1½	610	¾	3¼	4¼	2¾	.42
C-710-2	2	610	¾	3¾	4¾	3¾	.52
C-710-2-1/2	2½	1,130	½	4½	5¾	3¾	.61
C-710-3	3	1,130	½	5	6¾	4¾	.90
C-710-3-1/2	3½	1,130	½	4½	6¾	3¾	.99
C-710-4	4	1,430	¾	5¾	7¾	4¾	1.40
C-710-5	5	1,430	¾	6	8¾	5	2.10
C-710-6	6	1,940	¾	7	10½	5¾	3.00

Standard Finish — GoldGalv®, unless otherwise stated.

CAT. NO.	PIPE SIZE (IN.)	MAX. LOAD (LBS.)	A (IN.)	B (IN.)	C (IN.)	ROD TAKE OUT E (IN.)	WT. EACH (LBS.)
C-710-7	7	2,000	¾	7¾	11¾	6½	5.42
C-710-8	8	2,000	¾	8½	12¾	6¾	5.25
C-710-10	10	3,600	¾	10	15¾	8¼	9.10
C-710-12	12	3,800	¾	11¾	17½	9¼	11.75
C-710-14	14	4,200	1	12½	19¾	10¾	14.25
C-710-16	16	4,800	1	15	23	13¾	20.75
C-710-18	18	4,800	1¼	15¾	24¾	13¾	23.00
C-710-20	20	4,800	1¼	17¾	27¾	15¾	41.50
C-710-24	24	4,800	1¼	19¾	31¾	17½	50.00
C-710-30	30	6,000	1¼	24¾	40¾	21¾	68.08
C-710-36	36	9,500	1½	32¾	50¾	30	68.68

Standard Finish — GoldGalv®, unless otherwise stated.