

## ALUMINUM COMPRESSION SPLICES

**KL**

### Type KL Compression Sleeves, 840 Die

| Cat. No. | End "A" Conductor Range              |            | End "B" Conductor Range            |            |
|----------|--------------------------------------|------------|------------------------------------|------------|
|          |                                      | Color Code |                                    | Color Code |
| KL20-1   | 6str<br>6 str compact                | Blue       | 6 str<br>6 str compact             | Blue       |
| KL22-1   | 4 str<br>4 str compact               | Orange     | 4 str<br>4 str compact             | Orange     |
| KL25-1   | 2 str<br>2 str compact               | Red        | 2 str<br>2 str compact             | Red        |
| KL31-1   | 1/0 sol Al, 1 str<br>1/0 str compact | Red        | 1/0 sol Al, 1 str<br>1 str compact | Red        |
| KL36-1   | 1/0 str<br>2/0 str compact           | Yellow     | 1/0 str<br>2/0 str compact         | Yellow     |
| KL45-1   | 2/0 str<br>3/0 str compact           | Gray       | 1-2 str<br>1str compact            | Red        |
| KL46-1   |                                      |            | 0 str<br>2/0 str compact           | Yellow     |
| KL47-1   |                                      |            | 2/0 str<br>3/0 str compact         | Gray       |
| KL54-1   | 3/0 str<br>4/0 str compact           | Black      | 3-4 str<br>2 sol                   | Orange     |
| KL55-1   |                                      |            | 1-2 str<br>1 str compact           | Red        |
| KL56-1   |                                      |            | 1/0 str<br>2/0 str compact         | Yellow     |
| KL57-1   |                                      |            | 2/0 str<br>3/0 str compact         | Gray       |
| KL58-1   |                                      |            | 3/0 str<br>4/0 str compact         | Black      |
| KL64-1   | 4/0 str                              | Pink       | 3-4 str<br>2 sol                   | Orange     |
| KL65-1   |                                      |            | 1-2 str<br>1 str compact           | Red        |
| KL66-1   |                                      |            | 1/0 str<br>2/0 str compact         | Yellow     |
| KL67-1   |                                      |            | 2/0 str<br>3/0 str compact         | Gray       |
| KL68-1   |                                      |            | 3/0 str<br>4/0 str compact         | Black      |
| KL69-1   |                                      |            | 4/0 str                            | Pink       |

See Technical Reference of further information.



- For combinations of aluminum-aluminum and aluminum-copper conductors.
- Splices large conductors required for commercial service; use as low cost reducing sleeve.
- All sizes can be installed with popular mechanical and hydraulic tools.
- Center stop assures proper conductor positioning.
- Meet ANSI C 119.4 Requirements
- Install with standard compression dies.

| Cat. No. | Installation Dies         |                         |
|----------|---------------------------|-------------------------|
|          | Mech.                     | Hyd.                    |
| All      | 840, W-K840, EEI,-11A, TX | 840, U-K840 U249, B49EA |