

Pipe straps, pipe and conduit clamps and hangers

Conduit and cable clamps




Standard

C711 "J" Pipe hanger

Pipe size (in.)	A rod size (in.)	B (in.)	C (in.)	Overall dimension D (in.)	E (in.)	F (in.)	Bolt size (in.)	G (in.)	Thickness	Width (in.)	Max. rec. load lb	Approx. Wt./C lb
1/2	3/8	2 5/8	1 3/4	7/16	1 1/2	1 15/16	1/4	3 7/32	12 ga	3/4	400	18
3/4	3/8	2 7/8	1 7/8	7/16	1 11/16	2 1/8	1/4	3 1/2	12 ga	3/4	400	21
1	3/8	2 15/16	1 15/16	7/16	1 13/16	2 5/16	1/4	3 11/16	12 ga	3/4	400	22
1 1/4	3/8	3 1/4	2	7/16	2 1/16	2 5/8	1/4	4 1/8	12 ga	3/4	400	25
1 1/2	3/8	3 9/16	2 3/16	7/16	2 7/16	2 7/8	1/4	4 5/8	12 ga	3/4	400	27
2	3/8	3 11/16	2 1/8	7/16	2 9/16	3 1/16	1/4	5	12 ga	3/4	400	29
2 1/2	1/2	4 7/16	2 7/16	9/16	3 3/16	3 5/8	3/8	6	12 ga	1 1/4	500	64
3	1/2	4 13/16	2 9/16	9/16	3 1/2	4 1/16	3/8	6 21/32	12 ga	1 1/4	500	72
3 1/2	1/2	5 1/8	2 5/8	9/16	3 3/4	4 3/8	3/8	7 1/16	3/16	1 1/4	500	84
4	5/8	6 1/8	3 3/16	9/16	4 5/8	5 1/16	3/8	8 9/16	3/16	1 1/4	550	138
5	5/8	6 3/4	3 1/4	9/16	5 1/16	5 5/8	3/8	9 27/32	3/16	1 1/4	550	162
6*	3/4	7 3/4	3 9/16	9/16	5 13/16	6 5/8	3/8	11 1/4	3/16	1 1/4	600	249
8*	7/8	9 1/16	3 11/16	9/16	6 15/16	8	3/8	13 11/16	3/16	1 1/4	760	291

Diagram



*Hangers 6 in. and over have hole instead of slot.

Standard finishes – GoldGalv®, electrogalvanized (EG)

Complies with specification MSS SP69, Type 5. Hole provided for side mounting to wall as bracket.

Example: C711-1/2