


PRODUCT-DETAILS

3120

2 INCH INSUL TITE BITE CONNECTOR ST



General Information

Extended Product Type	3120
Product ID	7TAA106030R0007
EAN	5414363140825
Catalog Description	2 INCH INSUL TITE BITE CONNECTOR ST
Long Description	Metal-Clad and Armored Cable Fitting, Straight, Trade Size 2 Inch, Knockout Size 2 Inch, Cable Range 2.312 to 2.500 Inch, Malleable Iron with Zinc Plating, Nylon Insulated

Ordering

EAN	5414363140825
-----	---------------

Dimensions

Product Net Weight	1.59 lb 721.088 g
--------------------	----------------------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	5 in 127 mm
Package Level 1 Height	3 in 76 mm

Package Level 1 Depth / Length	4.5 in 114 mm
Package Level 2 Units	5 piece
Package Level 2 Width	5.4 in 137 mm
Package Level 2 Height	7 in 178 mm
Package Level 2 Depth / Length	21.6 in 549 mm

Additional Information

Application	For Use with Armored Cable and Flexible Metal Conduit.
Brand / Label	T&B Cord & Cable Fittings
Color	Metallic
Insulation Material	Nylon
Material	Malleable Iron
Number of Batteries	0
Product Name	INSULATED CONDUIT JOINT
Product Type	Armored Cable/Flexible Metal Conduit Fittings
Size	2 Inch
Special Functions	Unique Saddle Design Firmly Secures Cable In Place, Provides Holding Power In Excess of Listing Agency Requirements and Assures High Quality Bonding
Standards	UL E23018, CSA 2884
Surface Finishing	Electro Zinc Plated
UPC	786210031200

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	3120
Instructions and Manuals	3120

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121419
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4573 >> Flex connectors

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

