

## Color-coded compression connectors

### Type CSP – Copper splices, short barrel



#### Copper compression connectors

- For use with copper conductors: AWG stranded, flexible cable, welding cable and portable cord
- Specially designed for industrial and building applications
- Made of high-conductivity seamless copper tubing
- Tin-plated for corrosion resistance
- Specially chamfered barrel for ease of installation
- Color-coded for matching die identification
- Can be used for medium voltage application up to 35 kV, provided proper insulation techniques are used

- CSA certified and UL listed for AWG conductors when installed with Blackburn, Burndy, ABB or Anderson tools, as specified by CSA
- Comply with Subpart 111.60-17 of Federal Register's Coast Guard Electrical Engineering Rules and Regulations

#### Short barrel connectors

- Short barrel connectors designed for regular-duty applications
- Ideal for confined areas

#### Type CSP – Copper splices, short barrel



Cat. no.	Conductor size (Cu)	Length (in.)	Color code
CSP8	8 str.	1	Red
CSP6	6 str.	1	Blue
CSP4	4 str.	1	Gray
CSP2	2 + 3 str.	1¼	Brown
CSP1	1 str.	1½	Green
CSP10	1/0 str.	1⅝	Pink
CSP20	2/0 str.	1¾	Black
CSP30	3/0 str.	1¾	Orange
CSP40	4/0 str.	1⅞	Purple
CSP250	250 kcmil	2¼	Yellow
CSP300	300 kcmil	1⅞	White
CSP350	350 kcmil	2¼	Red
CSP400	400 kcmil	2¾	Blue
CSP500	500 kcmil	2¾	Brown
CSP600	600 kcmil	3	Green
CSP750	750 kcmil	3	Black
CSP1000	1,000 kcmil	3⅝	

See the Color-Keyed tools, dies and kits catalogue for more tool and die information.

Blackburn and ABB are registered trademarks of ABB Installation Products, Ltd.  
All other trademarks are the property of their respective owners.