


Industrial Circuit Breakers

Quick Reference Guide 10-1200A Circuit Breakers Thermal Magnetic Trip



TEYD, TEYH, TEYL

Ratings do not apply to molded case switches.

Maximum interruption ratings and voltages shown. A circuit breaker of the type given in the left-hand column may be applied at the given circuit voltage in any electrical distribution system where the available fault current at the load terminals of the breaker does not exceed the value in the table.

That circuit breaker type may also be applied at intermediate values of circuit voltage provided the available fault current at the load terminals of the breaker does not exceed the value in the table for the higher value of voltage.

TEY and TEYF (UL/cUL File E-11592; TEYD/H/L (UL/cUL File E-11592)

Circuit Breaker Type	Ampere Rating	No. Poles	Maximum Voltage Rating		UL Listed Interrupting Ratings—rms Symmetrical kA												Dimensions (in.)							Approx. Ship Wt./Std. Pack
			Vac										Vdc											
			ac	dc	120	120/240	240	277	480/277	480	600	125	250	500	H	W	D	A	B	C	E			
TEY ^{2,3}	15-100	1	277	125	65	—	14	14	—	—	—	10	—	—	5 1/4	1	3 1/16	—	—	—	—	—		
		2	480/277	250	—		—	65	14	14		—	—	—		10							—	2
		3	—	—	—		—	—	—	—		—	—	—		—							3	
TEYF ^{2,3}	15-60	1	277	125	65	—	18	18	—	—	—	10	—	—	5 1/4	1	3 1/16	—	—	—	—	—		
	2	480/277	250	—	—		65	18	18	—		—	—	10		—							2	
	3	—	—	—	—		—	—	—	—		—	—	—		—							3	
TEYD	15-70	1	277	—	65	65	—	25	—	—	—	—	—	—	5 1/4	1	3 1/16	—	—	—	—	1 lb		
	2	480/277	—	—	65	65	—	25	—	—	—	—	—	2		2 lb								
	3	—	—	—	—	—	—	—	—	—	—	—	—	3		2.7 lb								
TEYH	15-70	1	277	—	65	65	—	35	—	—	—	—	—	—	5 1/4	1	3 1/16	—	—	—	—	1 lb		
	2	480/277	—	—	65	65	—	35	—	—	—	—	—	2		2 lb								
	3	—	—	—	—	—	—	—	—	—	—	—	—	3		2.7 lb								
TEYL	15-70	1	277	125	100	100	—	65	—	—	—	15	—	—	5 1/4	1	3 1/16	—	—	—	—	1 lb		
	2	480/277	250	—	100	100	—	65	—	—	42	20	—	2		2 lb								
	3	—	—	—	—	—	—	—	—	—	42	35	—	3		2.7 lb								

E150 (UL/cUL File E-11592)

TEB ^{2,3}	10-100 ⁴	1	120	125	10	-	-					5	-	-	6 5/16	1 3/8	3 3/8	2 41/64	2 15/64	-	23/32	26 lb/24
		2	240	250	-		10	-	-	-	-	-	5	-		2 3/4						24 lb/12
		3		-	-		10					-	-	-		4 1/8						28 lb/8
TED ^{2,3}	10-100 ⁴	1	277, 347 ⁵	125		-	-	14	-	10	-	10	-	-	6 5/16	1 3/8	3 3/8	2 41/64	2 15/64	-	23/32	26 lb/24
	2	480	250		18		-	-	18	-	-	10	-	2 3/4		24 lb/12						
	3 ⁷	480, 600	500							14	-	10	10 ¹	4 1/8		28 lb/8						
THED ^{2,3}	15-30	1	277, 347 ⁵	125		-	-	65	-	-	-	10 ⁶	-	-	6 5/16	1 3/8	3 3/8	2 41/64	2 15/64	-	23/32	26 lb/24
	15-100	2	480	250			65				-		10 ⁶	-		24 lb/12						
	20-100						65	-	-	25												28 lb/8
	110-150	3 ⁷	600	500			42				18	-	10	10 ¹		4 1/8						28 lb/8

Mag-Break (UL Files E-11592, E-66390; Magnetic Trip Unit)⁸

TJC	400-600	3	600	-	-	-	42	-	-	30	22	-	-	-	10 1/8	8 1/4	3 13/16	3 13/16	3 13/16	1 3/8	16 lb/1
																					17 1/2 lb/1

¹UL listed with poles in series for 500 Vdc ungrounded battery applications.

²UL listed as HACR (heating, air conditioning, and refrigeration).

³15-50A UL listed as HID (high intensity discharge).

⁴10 amp not UL listed, rated 5kA @ 120V, 240V and 480V

⁵UL/cUL listed for 10kA @ 347 Vac (TED) and 18kA @ 347V (THED).

Rated 10kA @ 480V but not UL listed.

⁶UL listed 10kA, GE tested to 20kA.

⁷TED, 3P, 600V, 15A breaker is obsolete. (TED136015WL & THED136015WL)

⁸Per UL 489, interrupting capacities are not shown on product label.

Industrial Circuit Breakers

15-100A


Thermal Magnetic Trip

Type TEY/TEYF

Noninterchangeable Trip

Bolt-on

480Y/277V Class



1- 2- and 3-pole TEY/TEYF breakers

TEY and TEYF breakers are one-inch wide per pole, compact, bolt-on circuit breakers for use on grounded 480Y/277 Vac systems. Short circuit ratings at that voltage for TEY and TEYF are 14 and 18kA, respectively. TEYF also offers higher selectivity ratings with upstream devices (See DET-537 for details). The bolt-on mounting base (TEY3B) shown on page 6-217 makes TEY and TEYF suitable for various lug-lug applications.

TEY/TEYF (UL/cUL File E-11592)

Ampere Rating	Wire Range ¹	Product Number	Product Number
Single Pole - Includes Integral Cu/Al Load Lugs		Type TEY^{3,4} 14kA @ 277 Vac	Type TEYF^{3,4} 18kA @ 277 Vac
15	#14-#10	TEY115 ²	TEYF115 ²
20	#14-#10	TEY120 ²	TEYF120 ²
25	#14-#10	TEY125	TEYF125
30	#14-#10	TEY130	TEYF130
35	#10-#4	TEY135	TEYF135
40	#10-#4	TEY140	TEYF140
45	#10-#4	TEY145	TEYF145
50	#10-#4	TEY150	TEYF150
60	#10-#4	TEY160	TEYF160
70	#4-1/0	TEY170	—
80	#4-1/0	TEY180	—
90	#4-1/0	TEY190	—
100	#4-1/0	TEY1100	—
Two-Pole - Includes Integral Cu/Al Load Lugs		Type TEY^{3,4} 14kA @ 480 / 277 Vac	Type TEYF^{3,4} 18kA @ 480 / 277 Vac
15	#14-#10	TEY215	TEYF215
20	#14-#10	TEY220	TEYF220
25	#14-#10	TEY225	TEYF225
30	#14-#10	TEY230	TEYF230
35	#10-#4	TEY235	TEYF235
40	#10-#4	TEY240	TEYF240
45	#10-#4	TEY245	TEYF245
50	#10-#4	TEY250	TEYF250
60	#10-#4	TEY260	TEYF260
70	#4-1/0	TEY270	TEYF270
80	#4-1/0	TEY280	TEYF280
90	#4-1/0	TEY290	TEYF290
100	#4-1/0	TEY2100	TEYF2100
110	#4-2/0	—	TEYF2110B
125	#4-2/0	—	TEYF2125B
Three-Pole - Includes Integral Cu/Al Load Lugs		Type TEY^{3,4} 14kA @ 480 / 277 Vac	Type TEYF^{3,4} 18kA @ 480 / 277 Vac
15	#14-#10	TEY315	TEYF315
20	#14-#10	TEY320	TEYF320
25	#14-#10	TEY325	TEYF325
30	#14-#10	TEY330	TEYF330
35	#10-#4	TEY335	TEYF335
40	#10-#4	TEY340	TEYF340
45	#10-#4	TEY345	TEYF345
50	#10-#4	TEY350	TEYF350
60	#10-#4	TEY360	TEYF360
70	#4-1/0	TEY370	TEYF370
80	#4-1/0	TEY380	TEYF380
90	#4-1/0	TEY390	TEYF390
100	#4-1/0	TEY3100	TEYF3100
110	#4-2/0	—	TEYF3110B
125	#4-2/0	—	TEYF3125B

¹Solid or stranded for 14-10 AWG.²Single-pole, 15 and 20 ampere breakers are also UL listed as switching duty breakers, suitable for switching 120, 240, or 277 Vac.³UL listed HACR (Heating, Air Conditioning, Refrigeration).⁴UL listed for HID (high intensity discharge), all 50A or less.