# 2.94 in (75 mm)



Shown actual size: Skylark dimmer and

1-gang Claro wallplate in White (WH).

# **Product family features**

- · Rocker switch returns light to light level indicated by slider on preset dimmers
- Slide up to brighten, down to dim
- · LED+ models available
- Coordinating Claro and Stainless Steel wallplates only available separately
- · All models must be derated unless otherwise noted. Visit lutron.com/multigang for more information.

# **Control types**

Single-pole (1 location)

回点面 3-way or 4-way (2 or more locations)

# **Direct load type compatibility**

- Dimmable LED/CFL lighting (screw-base)
- Incandescent/halogen lighting
- ▼ Magnetic low-voltage lighting
- ☐ Electronic low-voltage lighting
- LED lighting
- □ Fluorescent lighting
- Ceiling fans
- ★ Ceiling fan/lights

# Load type requiring load interface

Neon/cold cathode lighting

Lighting load interfaces may be applicable for some additional load type, voltage, and capacity combinations. For additional information see "Lighting Load Interfaces."

### **Available finishes**

Use **BOLD** color code in model number (Example: S-600P-**GR**) Gloss



### Metal wallplates\*



Stainless Steel

Stainless Steel metal wallplate only available separately and includes black plastic trim/adapter, visible from side. Match with separate Black (BL) control.

# Dual slide-to-off dimmer (two loads)



# **Dimmers** (left/right)

Slide up to on/brighten, down to dim/off

# **⊘**/**⊘** Incandescent/halogen dimmer

### Dual slide-to-off dimmer

Incandescent/halogen

S2-L-**XX**<sup>1</sup> Single-pole 120V 300W dimmer (left) Incandescent/halogen 300W dimmer (right)

# Slide-to-off fan controls



- · Slide up to on/increase speed, down to decrease/off
- 3 quiet fan speeds designed to prevent motor hum (for use with only one ceiling paddle fan)
- Fully variable model also available (for use with multiple ceiling paddle or exhaust fans)

### **¥** Fan controls

# Slide-to-off fan controls-quiet 3-speed

Single-pole	SFSQ-F-XX1
120V 1.5A	
Single-pole	SFSQ-F-HO-XX1
120V 2A	

SFSQ-F-HO model for use with Hunter Original Series fans.

No derating required if ganged.

# Slide-to-off fan control—fully variable

Single-pole	SFS-5E- <u><b>XX</b></u> 1
120V 5A	

Control provides an additional wire for fan light switching (360 W, incandescent/halogen). Light turns on when fan is on, and off when fan is off. Fully variable fan controls are commonly known as solid state fan controls.

# Slide-to-off fan/light control with on/off light switch

(two loads)

# 

# Fan control (top)

- Slide up to on/increase speed, down to decrease/off
- 3 quiet fan speeds designed to prevent motor hum (for use with only one ceiling paddle fan)

# **Switch** (bottom)

· Rocker switch turns light on/off

SFSQ-LF-XX1

# **※ Fan control/light control**

Slide-to-off fan/light control—quiet 3-speed with on/off light switch (two loads)

Single-pole 120V 1.5A fan (top)

360W switch (bottom) Incandescent/halogen

No derating required if ganged.

# Dual slide-to-off fan/light control (two loads)

# 1.1 TP

# Fan control (left)

Slide up to on/increase speed, down to decrease/off

# **Dimmer** (right)

 Slide up to on/brighten, down to dim/off

# **★ Fan/light controls**

### Dual slide-to-off fan/light control—quiet 3-speed

Single-pole

S2-LFSQ-XX1

120V 1.5A fan (left)

300 W dimmer (right)

Incandescent/halogen

No derating required if ganged.

# Dual slide-to-off fan/light control-fully variable

Single-pole

S2-LF-XX1

120V 2.5A fan (left)

300W dimmer (right)

Incandescent/halogen

Fully variable fan controls are commonly known as solid state fan controls.

### Replacement knobs

Standard knob SK-XX<sup>2</sup> Contact Customer Service Split knobs

XX1: Gloss color codes

Wallplates not included. Order separately.

XX1: Gloss color codes

**XX**<sup>2</sup>: Available in Gloss White, Ivory, Almond, and Light Almond

38