



Shown actual size: Ariadni dimmer and 1-gang Fassada wallplate in White (WH).

Product family features

- Matches existing switches
- Toggle-style switch turns light on to level set by slider
- Slider adjusts light to your favorite level
- LED+ models available
- Coordinating Fassada wallplates only available separately
- All models must be derated unless otherwise noted. Visit [lutron.com/multigang](https://lutron.com/multigang) for more information.

Control types

- Single-pole (1 location)
- 3-way or 4-way (2 or more locations)

Direct load type compatibility

- Dimmable LED/CFL lighting (screw-base)
- Incandescent/halogen lighting
- Magnetic low-voltage lighting
- LED lighting
- Fluorescent lighting
- Ceiling fans
- Ceiling fan/lights

Load type requiring load interface

- Electronic low-voltage lighting
- Neon/cold cathode lighting

Lighting load interfaces may be applicable for some additional load type, voltage, and capacity combinations. For additional information, see "Lighting Load Interfaces."

Available finishes

Use **BOLD** color code in model number (Example: AY-600P-**BL**)  
Gloss



Metal wallplate\*



**SS**  
Stainless Steel

\* Stainless Steel metal wallplate only available separately and includes black plastic trim/adaptor, visible from side. Match with separate Black (BL) control.

Preset dimmers



- Toggle turns lights on/off
- Slide up to brighten, down to dim
- LED+ dimmers provide reliable dimming of dimmable LEDs/CFLs, as well as halogens and incandescents



Incandescent/halogen dimmers

Preset dimmers with locator light

Single-pole	AY-600PNL- <b>XX</b> <sup>2</sup>
120V 600W	
Single-pole	AY-10PNL- <b>XX</b> <sup>2</sup>
120V 1000W	
3-way	AY-603PNL- <b>XX</b> <sup>2</sup>
120V 600W	
3-way	AY-103PNL- <b>XX</b> <sup>2</sup>
120V 1000W	



Magnetic low-voltage dimmers

Preset dimmers

Single-pole	AYLV-600P- <b>XX</b> <sup>1</sup>
120V 600 VA (450 W)	
3-way	AYLV-603P- <b>XX</b> <sup>1</sup>
120V 600 VA (450 W)	

The stated VA (volt-ampere) rating includes the magnetic transformer heat losses and the lamp load. The stated W (watt) rating is the maximum lamp wattage based on assumed 20% transformer loss.



3-wire LED driver/fluorescent ballast dimmers

Preset dimmers

3-way/single-pole	AYF-103P- <b>XX</b> <sup>1</sup>
120V 8A	
3-way/single-pole	AYF-103P-277- <b>XX</b> <sup>1</sup>
277V 6A	

Adjustable low-end trim.

No derating required if ganged.



Incandescent/halogen dimmers

Preset dimmers

Single-pole	AY-600P- <b>XX</b> <sup>1</sup>
120V 600W	
Single-pole	AY-10P- <b>XX</b> <sup>1</sup>
120V 1000W	
3-way	AY-603P- <b>XX</b> <sup>1</sup>
120V 600W	
3-way	AY-103P- <b>XX</b> <sup>1</sup>
120V 1000W	

**XX**<sup>1</sup>: Gloss color codes

**XX**<sup>2</sup>: Available in Gloss White (WH), Ivory (IV), Almond (AL) and Light Almond (LA)

Wallplates not included. Order separately.

Fan control



- Toggle turns fans on/off
- Slide up to increase speed, down to decrease
- 3 quiet fan speeds for increased comfort
- For use with only one ceiling paddle fan
- Designed to prevent motor hum



Fan control

Fan control—quiet 3-speed

3-way/single-pole	AYFSQ-F- <b>XX</b> <sup>1</sup>
120V 1.5A	

No derating required if ganged.

Dual fan/light control

(two loads)



Fan control (left)

- Use slider to turn fan on/off and adjust fan speed
- 3 quiet fan speeds for increased comfort
- For use with only one ceiling paddle fan
- Designed to prevent motor hum

Dimmer (right)

- Toggle turns light on/off
- Slide up to brighten, down to dim



Dual fan/light control

Fan/light control—quiet 3-speed

Single-pole	AY2-LFSQ- <b>XX</b> <sup>1</sup>
120V 1.5A fan (left)	
120V 300W dimmer (right)	
Incandescent/halogen	

No derating required if ganged.

**XX**<sup>1</sup>: Gloss color codes

Wallplates not included. Order separately.