Eaton 170M5884

Catalog Number: 170M5884

Eaton Bussmann series high speed square body fuse, 690V (IEC), 350A, 200 kAIC, Top fuse status indicator, Fuse, Blade end X Din 43-620 blade end, Class gR, DIN 43 620

General specifications



Eaton Bussmann series high speed

square body fuse

UPC

051712334235

Product Height

80 mm

Product Weight

421.3333333 g

Certifications

UL Recognized IEC Rated Catalog Number

170M5884

EAN

5027590461122

Product Length/Depth

210 mm

Product Width

160 mm

Compliances

CE Marked

RoHS Compliant



default Taxonomy Attribute Label

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers **Amperage Rating** 350 A Breaking capacity 200 kA Fuse indicator Top fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization category gR (general purpose semiconductor protection) Voltage type AC Fuse size 2 Rated voltage AC 690 V Current type AC Class Class gR Clearing (I2T) 135000 at 600 V Watt losses 50 W Fuse shape Square body, knife blade contacts Pre arc (I2T) 26000 Color

None

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-

Interrupt rating

200 kAIC

Fitted with:

Type T Indicator for micro

Connection

Blade end x Din 43-620 blade end

Construction size

2

Packaging type

Standard

Voltage rating

690 V (IEC)

Fuse type

DIN 43620

T indicator for micro

Bladed

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.

