

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : General Single-Phase

Product code : 10022071
Catalog # : 5036ES1BB56C

Frame : B56C
Output : 0.5 HP (0.37 kW)
Poles : 2
Frequency : 60 Hz
Rated voltage : 115/208-230 V
Rated current : 7.60/3.80-3.80 A
L. R. Amperes : 42.6/21.3-21.3 A
LRC : 5.6x(Code L)
No load current : 5.60/2.41-2.80 A
Rated speed : 3480 rpm
Slip : 3.33 %
Rated torque : 0.754 ft.lb
Locked rotor torque : 320 %
Breakdown torque : 280 %
Insulation class : B
Service factor : 1.15
Moment of inertia (J) : 0.0316 sq.ft.lb

Locked rotor time : 10s (cold) 6s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 55.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 25.4 lb

Output	25%	50%	75%	100%
Efficiency (%)	41.2	45.0	52.0	58.0
Power Factor	0.33	0.56	0.66	0.73

Foundation loads
Max. traction : 8 lb
Max. compression : 33 lb

	Drive end	Non drive end
Bearing type	6203 ZZ	6202 ZZ
Sealing	V'Ring	V'Ring
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	25/03/2024			
		Revision		