

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Standard Efficiency Three-Phase

Product code :

12686562

Catalog # :

02512ES3EOW324T-W22

Frame	: 324/6T	Locked rotor time	: 28s (cold) 16s (hot)
Output	: 25 HP (18.5 kW)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 208-230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 69.0-62.4/31.2 A	Protection degree	: IP55
L. R. Amperes	: 400-362/181 A	Cooling method	: IC411 - TEFC
LRC	: 5.8x(Code G)	Mounting	: F-2
No load current	: 27.6-25.0/12.5 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 1125 rpm	Noise level <sup>2</sup>	: 62.0 dB(A)
Slip	: 6.25 %	Starting method	: Direct On Line
Rated torque	: 117 ft.lb	Approx. weight <sup>3</sup>	: 566 lb
Locked rotor torque	: 300 %		
Breakdown torque	: 0 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 10.4 sq.ft.lb		
Design	: D		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	84.9	85.5	88.5	88.5	Max. traction	: -282 lb
Power Factor	0.45	0.69	0.79	0.84	Max. compression	: 282 lb

		Drive end	Non drive end
Bearing type	:	6312 C3	6212 C3
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	20000 h	20000 h
Lubricant amount	:	21 g	13 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	26/03/2024			
			Revision	