

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : General NEMA Premium Efficiency Three-Phase

Product code : 11139870

Catalog # : 00158OT3E145TF2

Frame : E143/5T
Output : 1.5 HP (1.1 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 230/460 V
Rated current : 4.40/2.20 A
L. R. Amperes : 39.6/19.8 A
LRC : 9.0x(Code M)
No load current : 2.80/1.40 A
Rated speed : 1740 rpm
Slip : 3.33 %
Rated torque : 4.53 ft.lb
Locked rotor torque : 360 %
Breakdown torque : 340 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 0.1597 sq.ft.lb
Design : B

Locked rotor time : 27s (cold) 15s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP21
Cooling method : IC01 - ODP
Mounting : F-2
Rotation¹ : Both (CW and CCW)
Noise level² : 52.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 44.4 lb

Output	25%	50%	75%	100%
--------	-----	-----	-----	------

Efficiency (%)	81.3	82.5	85.5	86.5
Power Factor	0.29	0.52	0.66	0.75

Foundation loads

Max. traction : 112 lb
Max. compression : 156 lb

	Drive end	Non drive end
Bearing type	6205 ZZ	6204 ZZ
Sealing	Without Bearing Seal	Without Bearing Seal
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	Mobil Polyrex EM	

Notes:

USABLE @208V 4.50A SF 1.00 SFA 4.50A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	25/03/2024			
		Revision		