DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer Product line : Rolled Steel Single-Phase Product code: 13188600 Catalog #: .5036OT1BW56-S Frame : W56 Locked rotor time : 16s (cold) 9s (hot) Output : 0.5 HP (0.37 kW) Temperature rise : 80 K Poles Duty cycle : Cont.(S1) : 2 Frequency : 60 Hz Ambient temperature : -20°C to +40°C : 115/208-230 V : 1000 m.a.s.l. Rated voltage Altitude Rated current Cooling method : IC01 - ODP : 4.80/2.65-2.40 A L. R. Amperes : 42.2/23.3-21.1 A Mounting : F-1 **LRC** : 8.8x(Code L) Rotation¹ : Both (CW and CCW) No load current : 1.60/0.690-0.800 A Noise level² : 56.0 dB(A) Rated speed : 3510 rpm Starting method : Direct On Line Slip : 2.50 % Approx. weight3 : 21.5 lb Rated torque : 0.748 ft.lb Locked rotor torque : 270 % Breakdown torque : 300 % : F Insulation class Service factor : 1.25 Moment of inertia (J) : 0.0254 sq.ft.lb Design : N 25% 50% 75% 100% Output Foundation loads Efficiency (%) 56.6 60.0 68.0 72.4 Max. traction : 11 lb Power Factor 0.94 : 32 lb 0.64 0.90 0.93 Max. compression Drive end Non drive end Bearing type 6203 ZZ 6202 ZZ Without Bearing Seal

Without Bearing Seal Sealing

Lubricant amount

Lubricant type Mobil Polyrex EM

Notes:

Lubrication interval

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

| Rev. | | Changes Summary | Performed | Checked | Date |
|--------------|------------|-----------------|-----------|---------|----------|
| | | | | | |
| Performed by | | | | | |
| Checked by | | | | Page | Revision |
| Date | 25/03/2024 | | | 1/1 | |