

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Single-Phase

Product code : 15761864
Catalog # : 00318OS1CCDOL184T-S

Frame	: 182/4T	Locked rotor time	: 10s (cold) 6s (hot)
Output	: 3 HP (2.2 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 208-230 V	Altitude	: 1000 m.a.s.l.
Rated current	: 13.7-12.8 A	Cooling method	: IC01 - ODP
L. R. Amperes	: 95.9-89.6 A	Mounting	: F-1
LRC	: 7.0x(Code H)	Rotation ¹	: Both (CW and CCW)
No load current	: 4.91-5.70 A	Starting method	: Direct On Line
Rated speed	: 1765 rpm	Approx. weight ³	: 66.6 lb
Slip	: 1.94 %		
Rated torque	: 8.93 ft.lb		
Locked rotor torque	: 275 %		
Breakdown torque	: 245 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.2781 sq.ft.lb		
Design	: L		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	73.0	80.0	81.5	Max. traction	: 106 lb
Power Factor	0.82	0.88	0.92	Max. compression	: 173 lb

	Drive end	Non drive end
Bearing type	: 6206 ZZ	: 6205 ZZ
Sealing	: Without Bearing Seal	: Without Bearing Seal
Lubrication interval	: -	: -
Lubricant amount	: -	: -
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1 Revision		
Checked by				
Date	26/03/2024			