

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Single-Phase

Product code : 13267061
Catalog # : .5036ES1BW56-S

Frame : W56
Output : 0.5 HP (0.37 kW)
Poles : 2
Frequency : 60 Hz
Rated voltage : 115/208-230 V
Rated current : 7.00/3.87-3.50 A
L. R. Amperes : 56.0/31.0-28.0 A
LRC : 8.0x(Code P)
No load current : 4.80/2.07-2.40 A
Rated speed : 3500 rpm
Slip : 2.78 %
Rated torque : 0.750 ft.lb
Locked rotor torque : 290 %
Breakdown torque : 300 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 0.0233 sq.ft.lb
Design : N

Locked rotor time : 12s (cold) 7s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 66.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 21.0 lb

Output	25%	50%	75%	100%
Efficiency (%)	48.1	50.0	58.0	60.0
Power Factor	0.34	0.59	0.69	0.76

Foundation loads
Max. traction : 11 lb
Max. compression : 32 lb

	Drive end	Non drive end
Bearing type	6203 ZZ	6202 ZZ
Sealing	V'Ring	Without Bearing Seal
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	25/03/2024			
		Revision		