

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Single-Phase

Product code : 13952797
Catalog # : 00336ES1E145T-S

Frame : 143/5T
Output : 3 HP (2.2 kW)
Poles : 2
Frequency : 60 Hz
Rated voltage : 208-230/460 V
Rated current : 14.0-12.7/6.35 A
L. R. Amperes : 112-102/50.8 A
LRC : 8.0x(Code J)
No load current : 3.45-4.00/2.00 A
Rated speed : 3490 rpm
Slip : 3.06 %
Rated torque : 4.51 ft.lb
Locked rotor torque : 210 %
Breakdown torque : 250 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 0.0944 sq.ft.lb
Design : L

Locked rotor time : 10s (cold) 6s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 68.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 49.1 lb

Output	50%	75%	100%
Efficiency (%)	76.0	79.0	80.0
Power Factor	0.86	0.92	0.94

Foundation loads
Max. traction : 73 lb
Max. compression : 123 lb

	Drive end	Non drive end
Bearing type :	6205 ZZ	6203 ZZ
Sealing :	V'Ring	Without Bearing Seal
Lubrication interval :	-	-
Lubricant amount :	-	-
Lubricant type :	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	26/03/2024			
		Revision		