

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Fan and Exhaust Premium
Efficiency Three-Phase

Product code : 13661000

Catalog # : 00158OT3ERB56-S

Frame : 56H
Output : 1.5 HP (1.1 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 230/460 V
Rated current : 4.20/2.10 A
L. R. Amperes : 37.0/18.5 A
LRC : 8.8x(Code L)
No load current : 2.60/1.30 A
Rated speed : 1760 rpm
Slip : 2.22 %
Rated torque : 4.48 ft.lb
Locked rotor torque : 290 %
Breakdown torque : 350 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 0.1296 sq.ft.lb
Design : A

Locked rotor time : 25s (cold) 14s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Cooling method : IC01 - ODP
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 52.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 41.2 lb

Output	25%		50%		75%		100%	
Efficiency (%)	82.9	84.3	84.0	83.7	85.5	84.7	86.5	83.6
	81.0		81.6		84.0		84.2	
Power Factor	0.30	0.36	0.53	0.61	0.66	0.74	0.76	0.81
	0.30		0.53		0.67		0.76	

Foundation loads
Max. traction : 160 lb
Max. compression : 201 lb

	Drive end	Non drive end
Bearing type :	6204 ZZ	6202 ZZ
Sealing :	Without Bearing Seal	Without Bearing Seal
Lubrication interval :	-	-
Lubricant amount :	-	-
Lubricant type :	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	26/03/2024			

Page 1 / 1
Revision