

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel High Efficiency Three-Phase Product code : 13199396

Frame	: 143/5TC	Locked rotor time	: 55s (cold) 31s (hot)
Output	: 1 HP (0.75 kW)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 200/400 V	Altitude	: 1000 m.a.s.l.
Rated current	: 3.82/1.91 A	Protection degree	: IP55
L. R. Amperes	: 24.1/12.0 A	Cooling method	: IC411 - TEFC
LRC	: 6.3x(Code K)	Mounting	: W-6
No load current	: 2.48/1.24 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 1145 rpm	Noise level <sup>2</sup>	: 50.0 dB(A)
Slip	: 4.58 %	Starting method	: Direct On Line
Rated torque	: 4.59 ft.lb	Approx. weight <sup>3</sup>	: 37.0 lb
Locked rotor torque	: 270 %		
Breakdown torque	: 320 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.1037 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads
Efficiency (%)	76.5	77.0	80.0	80.0	Max. traction : 109 lb
Power Factor	0.27	0.49	0.62	0.71	Max. compression : 146 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6205 ZZ	6203 ZZ
Sealing	:	V'Ring	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	26/03/2024			
			Revision	