

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel High Efficiency Three-Phase Product code : 12677350

Frame	: 213/5TC	Locked rotor time	: 64s (cold) 36s (hot)
Output	: 3 HP (2.2 kW)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 8.52/4.26 A	Protection degree	: IP55
L. R. Amperes	: 52.8/26.4 A	Cooling method	: IC411 - TEFC
LRC	: 6.2x(Code H)	Mounting	: W-6
No load current	: 4.93/2.46 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1175 rpm	Noise level ²	: 55.0 dB(A)
Slip	: 2.08 %	Starting method	: Direct On Line
Rated torque	: 13.4 ft.lb	Approx. weight ³	: 119 lb
Locked rotor torque	: 229 %		
Breakdown torque	: 280 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.8104 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads					
Efficiency (%)	85.2	86.4	85.5	85.6	87.5	86.2	87.5	85.0	Max. traction	: 178 lb
	84.1		84.3		86.1		85.9			
Power Factor	0.31	0.36	0.53	0.61	0.66	0.73	0.74	0.79	Max. compression	: 297 lb
	0.31		0.54		0.67		0.75			

					<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:				6208 ZZ	6206 ZZ
Sealing	:				V'Ring	Without Bearing Seal
Lubrication interval	:				-	-
Lubricant amount	:				-	-
Lubricant type	:				Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	26/03/2024			
			Revision	