

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel NEMA Premium Efficiency  
Three-Phase

Product code : 13662713

Catalog # : 02536ET3E256T-S

Frame : 254/6T  
Output : 25 HP (18.5 kW)  
Poles : 2  
Frequency : 60 Hz  
Rated voltage : 230/460 V  
Rated current : 57.0/28.5 A  
L. R. Amperes : 473/237 A  
LRC : 8.3x(Code J)  
No load current : 20.1/10.0 A  
Rated speed : 3530 rpm  
Slip : 1.94 %  
Rated torque : 37.2 ft.lb  
Locked rotor torque : 240 %  
Breakdown torque : 340 %  
Insulation class : F  
Service factor : 1.15  
Moment of inertia (J) : 1.31 sq.ft.lb  
Design : A

Locked rotor time : 14s (cold) 8s (hot)  
Temperature rise : 80 K  
Duty cycle : Cont.(S1)  
Ambient temperature : -20°C to +40°C  
Altitude : 1000 m.a.s.l.  
Protection degree : IP55  
Cooling method : IC411 - TEFC  
Mounting : F-1  
Rotation<sup>1</sup> : Both (CW and CCW)  
Noise level<sup>2</sup> : 75.0 dB(A)  
Starting method : Direct On Line  
Approx. weight<sup>3</sup> : 227 lb

Output	25%	50%	75%	100%
Efficiency (%)	90.8	91.0	91.7	91.7
Power Factor	0.50	0.77	0.85	0.89

Foundation loads  
Max. traction : 493 lb  
Max. compression : 720 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type :		6309 Z C3	6208 Z C3
Sealing :		V'Ring	Without Bearing Seal
Lubrication interval :		15797 h	20000 h
Lubricant amount :		13 g	8 g
Lubricant type :		Mobil Polyrex EM	

Notes:  
USABLE @208V 63.0A SF 1.00 SFA 63.0A

This revision replaces and cancel the previous one, which must be eliminated.  
(1) Looking the motor from the shaft end.  
(2) Measured at 1m and with tolerance of +3dB(A).  
(3) Approximate weight subject to changes after manufacturing process.  
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	27/03/2024			
		Revision		