

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel NEMA Premium Efficiency
Three-Phase

Product code : 12630848

Catalog # : 01018ET3E215T-S

Frame : 213/5T
Output : 10 HP (7.5 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 230/460 V
Rated current : 24.4/12.2 A
L. R. Amperes : 171/85.4 A
LRC : 7.0x(Code H)
No load current : 11.1/5.54 A
Rated speed : 1760 rpm
Slip : 2.22 %
Rated torque : 29.8 ft.lb
Locked rotor torque : 250 %
Breakdown torque : 300 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 1.07 sq.ft.lb
Design : B

Locked rotor time : 27s (cold) 15s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 60.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 127 lb

Output	50%	75%	100%
Efficiency (%)	91.0	91.0	91.7
Power Factor	0.67	0.78	0.84

Foundation loads
Max. traction : 441 lb
Max. compression : 569 lb

	Drive end	Non drive end
Bearing type	6208 ZZ	6206 ZZ
Sealing	V'Ring	Without Bearing Seal
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	Mobil Polyrex EM	

Notes:
USABLE @208V 27.0A SF 1.00 SFA 27.0A

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1Revision		
Checked by				
Date	26/03/2024			