

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel NEMA Premium Efficiency  
Three-Phase

Product code : 12636588

Catalog # : 01012ET3E256T-S

Frame : 254/6T  
Output : 10 HP (7.5 kW)  
Poles : 6  
Frequency : 60 Hz  
Rated voltage : 230/460 V  
Rated current : 27.6/13.8 A  
L. R. Amperes : 149/74.5 A  
LRC : 5.4x(Code G)  
No load current : 14.2/7.12 A  
Rated speed : 1175 rpm  
Slip : 2.08 %  
Rated torque : 44.7 ft.lb  
Locked rotor torque : 210 %  
Breakdown torque : 229 %  
Insulation class : F  
Service factor : 1.15  
Moment of inertia (J) : 2.83 sq.ft.lb  
Design : B

Locked rotor time : 54s (cold) 30s (hot)  
Temperature rise : 80 K  
Duty cycle : Cont.(S1)  
Ambient temperature : -20°C to +40°C  
Altitude : 1000 m.a.s.l.  
Protection degree : IP55  
Cooling method : IC411 - TEFC  
Mounting : F-1  
Rotation<sup>1</sup> : Both (CW and CCW)  
Noise level<sup>2</sup> : 59.0 dB(A)  
Starting method : Direct On Line  
Approx. weight<sup>3</sup> : 239 lb

Output	25%	50%	75%	100%
Efficiency (%)	90.0	90.2	91.0	91.0
Power Factor	0.33	0.57	0.69	0.75

Foundation loads  
Max. traction : 373 lb  
Max. compression : 612 lb

	Drive end	Non drive end
Bearing type	6309 Z C3	6208 Z C3
Sealing	V'Ring	Without Bearing Seal
Lubrication interval	20000 h	20000 h
Lubricant amount	13 g	8 g
Lubricant type	Mobil Polyrex EM	

Notes:  
USABLE @208V 30.5A SF 1.00 SFA 30.5A

This revision replaces and cancel the previous one, which must be eliminated.  
(1) Looking the motor from the shaft end.  
(2) Measured at 1m and with tolerance of +3dB(A).  
(3) Approximate weight subject to changes after manufacturing process.  
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 1		
Checked by				
Date	26/03/2024			