

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Premium Efficiency Three-Phase

Product code : 13484338

Catalog # : 00118ET3E56C-S

Frame : 56C
Output : 1 HP (0.75 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 230/460 V
Rated current : 2.94/1.47 A
L. R. Amperes : 25.3/12.6 A
LRC : 8.6x(Code M)
No load current : 1.78/0.890 A
Rated speed : 1765 rpm
Slip : 1.94 %
Rated torque : 2.98 ft.lb
Locked rotor torque : 280 %
Breakdown torque : 300 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 0.1232 sq.ft.lb
Design : B

Locked rotor time : 34s (cold) 19s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 52.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 37.2 lb

Output	25%		50%		75%		100%	
Efficiency (%)	81.0	82.5	82.5	82.2	84.0	83.7	85.5	82.9
	80.4		80.9		83.5		83.7	
Power Factor	0.30	0.36	0.52	0.62	0.66	0.74	0.75	0.81
	0.31		0.55		0.68		0.77	

Foundation loads
Max. traction : 98 lb
Max. compression : 135 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6204 ZZ	6202 ZZ
Sealing	:	V'Ring	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	27/03/2024			
			Revision	