

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Standard Efficiency Three-Phase

Product code : 12676239

Catalog # : .2536ES3E56-S

Frame : 56
 Output : 0.25 HP (0.18 kW)
 Poles : 2
 Frequency : 60 Hz
 Rated voltage : 208-230/460 V
 Rated current : 1.01-0.914/0.457 A
 L. R. Amperes : 6.46-5.85/2.92 A
 LRC : 6.4x(Code L)
 No load current : 0.431-0.500/0.250 A
 Rated speed : 3475 rpm
 Slip : 3.47 %
 Rated torque : 0.378 ft.lb
 Locked rotor torque : 250 %
 Breakdown torque : 300 %
 Insulation class : F
 Service factor : 1.15
 Moment of inertia (J) : 0.0389 sq.ft.lb

Locked rotor time : 108s (cold) 60s (hot)
 Temperature rise : 80 K
 Duty cycle : Cont.(S1)
 Ambient temperature : -20°C to +40°C
 Altitude : 1000 m.a.s.l.
 Protection degree : IP55
 Cooling method : IC411 - TEFC
 Mounting : F-1
 Rotation¹ : Both (CW and CCW)
 Noise level² : 68.0 dB(A)
 Starting method : Direct On Line
 Approx. weight³ : 17.2 lb

Output	50%	75%	100%
Efficiency (%)	46.0 55.3	52.5 62.0	57.5 64.8
	54.3	61.7	65.3
Power Factor	0.75 0.79	0.82 0.86	0.86 0.90
	0.73	0.82	0.87

Foundation loads
 Max. traction : 5 lb
 Max. compression : 22 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6203 ZZ	6202 ZZ
Sealing	:	V'Ring	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	27/03/2024			
		Revision		