

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12395532

Catalog # : 25012ET3H449T-W22

Frame : 447/9T
Output : 250 HP (185 kW)
Poles : 6
Frequency : 60 Hz
Rated voltage : 575 V
Rated current : 234 A
L. R. Amperes : 1425 A
LRC : 6.1x(Code G)
No load current : 96.0 A
Rated speed : 1185 rpm
Slip : 1.25 %
Rated torque : 1110 ft.lb
Locked rotor torque : 240 %
Breakdown torque : 240 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 145 sq.ft.lb
Design : B

Locked rotor time : 21s (cold) 12s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 70.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 2954 lb

Output	50%	75%	100%
Efficiency (%)	95.0	95.4	95.8
Power Factor	0.68	0.79	0.83

Foundation loads
Max. traction : 5611 lb
Max. compression : 8565 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
4.8	4.2	3.9	2.3	1.7	1.2	0.8

	Drive end	Non drive end
Bearing type	6322 C3	6319 C3
Sealing	WSeal	WSeal
Lubrication interval	11000 h	13000 h
Lubricant amount	60 g	45 g
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	28/03/2024			
			Page	Revision
			1 / 1	