DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer

Product line : W40 NEMA Premium Efficiency Three-

Product code: 16065108

25036OT3G445TS-Catalog #:

RFVFD

: 41s (cold) 23s (hot)

Frame : 444/5TS

Output : 250 HP (185 kW)

Poles : 2 Frequency : 60 Hz : 460 V Rated voltage Rated current : 284 A L. R. Amperes : 2414 A

LRC : 8.5x(Code J) No load current : 86.0 A Rated speed : 3571 rpm Slip : 0.81 % Rated torque : 368 ft.lb : 240 %

Locked rotor torque Breakdown torque : 290 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 28.6 sq.ft.lb Design : A

Locked rotor time

Temperature rise : 105 K : Cont.(S1) Duty cycle Ambient temperature : -20°C to +40°C

Altitude

: 1000 m.a.s.l. Protection degree : IP23 : IC01 - ODP Cooling method

Non drive end

Mounting : F-1 Rotation¹ : Both (CW and CCW)

Noise level² : 87.0 dB(A) Starting method : VFD Approx. weight3 : 1394 lb

Output 25% 50% 75% 100% Foundation loads

Efficiency (%) 92.3 94.5 94.8 95.0 Max. traction : 2145 lb Power Factor 0.54 0.75 0.83 0.86 : 3539 lb Max. compression

> Drive end 6314 C4

6212 Z C4 Without Bearing Seal Without Bearing Seal 1200 h 1200 h

10 g 10 g

Mobil Polyrex EM Lubricant type

Notes:

Bearing type

Lubrication interval

Lubricant amount

Sealing

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	26/03/2024			1/2	

DATA SHEET

	П
ш	Ш

Three Phase Induction Motor - Squirrel Cage									
Customer :									
\/-lt 440 407	7/000 040 V	Space heater infor	Space heater information						
Voltage: 110-127	7/200-240 V								
Rev.		Changes Summary	Performed	Checked	Date				
Performed by									
Checked by				Page	Revision				
Date	26/03/2024			2/2					