

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 14157409

Catalog # : 75018ET3G588/9-W22

Frame : 588/9T
Output : 750 HP (560 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 460 V
Rated current : 855 A
L. R. Amperes : 6156 A
LRC : 7.2x(Code H)
No load current : 320 A
Rated speed : 1790 rpm
Slip : 0.56 %
Rated torque : 2200 ft.lb
Locked rotor torque : 240 %
Breakdown torque : 250 %
Insulation class : F
Service factor : 1.00
Moment of inertia (J) : 347 sq.ft.lb

Locked rotor time : 52s (cold) 29s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 81.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 5767 lb

Output	25%		50%		75%		100%	
Efficiency (%)	96.1	96.1	96.3	96.2	96.6	96.5	96.7	96.5
	96.1	95.4	96.2	95.8	96.5	96.2	96.5	96.5
Power Factor	0.45	0.46	0.70	0.71	0.80	0.81	0.85	0.85
	0.42	0.39	0.67	0.64	0.78	0.76	0.84	0.82

Foundation loads
Max. traction : 10764 lb
Max. compression : 16531 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	3.9	4.2	4.2	4.2
	P2 (0,5;1,0)	2.7	3.0	3.0	3.0
	P3 (0,25;1,0)	2.3	2.4	2.4	2.4
	P4 (0,9;0,5)	2.2	2.3	2.3	2.3
	P5 (0,5;0,5)	1.3	1.4	1.4	1.4
	P6 (0,5;0,25)	0.9	1.0	1.0	1.0
	P7 (0,25;0,25)	0.5	0.5	0.5	0.5

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6322 C3	6319 C3
Sealing	:	Taconite Labyrinth	Taconite Labyrinth
Lubrication interval	:	6000 h	8000 h
Lubricant amount	:	60 g	45 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	29/03/2024			

Page 1 / 2
Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page		Revision
Checked by					
Date	29/03/2024				