DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer	:								
Product line		: W22 NEMA Premium Efficiency Three- Product code : Phase							
	i iia	i ilase				Catalog # :	00709ET3H256T-W22		
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor tor		: 254/6T : 7.5 HP (5.5 kW) : 8 : 60 Hz : 575 V : 8.88 A : 47.1 A : 5.3x(Code G) : 5.20 A : 880 rpm : 2.22 % : 44.8 ft.lb : 200 %				d rotor time erature rise eycle ent temperature e etion degree eg method ing on¹ level² eg method ag method x. weight³	: 59s (cold) 33s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-1 : Both (CW and CCW) : 54.0 dB(A) : Direct On Line : 293 lb		
Breakdown torq Insulation class Service factor Moment of inert Design	ue	: 2 : F : 1	.25 .43 sq.ft.lb						
Output	25%	50%	75%	100%	Foundat	ion loads			
Efficiency (%) Power Factor			87.5 0.63	87.5 0.71	Max. tra Max. co	ction mpression	: 390 lb : 683 lb		
Losses at norma	tive operati	ng poin	its (speed;tor	que), in	percentage of r	ated output power			
P1 (0,9;1,0)	P2 (0,5				P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25	
13.8	11.7				7.8	5.7	4.4	3.4	
Bearing type Sealing Lubrication interval Lubricant amount Lubricant type		: : : :	63 V 20	<u>re end</u> 309 C3 "Ring 3000 h 13 g	Mobil Polyre.	Non drive en 6209 C3 V'Ring 20000 h 9 g x EM	<u>u</u>		
Notes:									
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.						These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.			
Rev.			Changes Sur	nmary		Performed	Checked	Date	
Performed by							_		
Checked by							Page	Revision	
Date	29/03/2	024					1/1		