DATA SHEET



Three Phase Induction Motor - Squirrel Cage									
Customer	:								
Product line	: W22 Co Phase	ooling To	wer High	Efficiency 1	hree-	Product code : Catalog # :		14319076 00226EP3QCT213V-W	/22
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Breakdown torque Insulation class Service factor Moment of inertia	e	: 213/5T : 0.5 HP : 12 : 60 Hz : 460 V : 1.33 A : 4.66 A : 3.5x(Co : 1.14 A : 580 rpn : 3.33 % : 4.53 ft.I : 130 % : 250 % : F : 1.15 : 1.55 sq	n b)	Temp Duty of Ambie Altitud Proter Coolin Moun Rotati Noise Startii	ent temperature de ction degree ng method ting		: 162s (cold) 90s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-2 : Both (CW and CCW) : 49.0 dB(A) : Direct On Line : 162 lb	
Output Efficiency (%) Power Factor	25% 50 60.0 78.4 62 0.18 0.29 0.3	2.0 78.5 6			Max. tra	tion loads action empression		96 lb 259 lb	
Bearing type Sealing Lubrication interva Lubricant amount Lubricant type Notes:	: : : : :		<u>Drive e</u> 6308 V'Ri - -	2RS ing	bil Polyre	Non drive 6 6207 2F V'Ring - - x EM	RS		

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

DATA SHEET

		П
Ш		Ц

Three Pha	se Induction	<u> </u>			
Customer	:				
		Space heater info	rmation		
Voltage: 110-127	7/200-240 V	Space neater info	mation		
Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision

2/2

28/03/2024

Date