DATA SHEET

Three Phase Induction Motor - Squirrel Cage



				-	•				
Customer	:								
Product line	: W22 Phas	2 Cooling T	ower High	Efficiency 1	hree-	Product code :		12180236 07589EP3PCT404V-W22	·
						Catalog # :		J7569EF3FC1404V-W22	•
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Insulation class Service factor Moment of inertia	е	: 404/5 : 75 HP : 4 : 60 Hz : 200 V : 196 A : 1570 A : 8.0x(0 : 73.6 A : 1780 I : 211 ft. : 240 % : 280 % : F : 1.15 : 27.4 s	A Code J) A rpm 6		Temp Duty Ambi Altitu Prote Cooli Mour Rota Noise Starti	ection degree ng method nting		: 14s (cold) 8s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-2 : Both (CW and CCW) : 71.0 dB(A) : Direct On Line : 0.0 lb	
Output	25%	50%	75%	100%	Founda	ation loads			
Efficiency (%)		7 91.7 88.5			Max. tr		:	593 lb	
Power Factor		6 0.74 0.45				ompression	-	593 lb	
			Drive 6	end	1	Non drive er	 nd		

POLYREA ESTER OIL (WT/ ENS)

6316 2RS C3

WSeal

Notes:

Bearing type

Lubrication interval Lubricant amount Lubricant type

Sealing

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

6314 2RS C3

WSeal

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

DATA SHEET

	П
	ш

Three Phase Induction Motor - Squirrel Cage						
Customer	:					
Voltage: 110-127	7/200-240 V	Space heater informa	ation			
Voltage: 110-127	7200-240 V					
Rev.		Changes Summary	Performed	Checked	Date	
					_	
Performed by						
Checked by				Page	Revision	
Date	28/03/2024			2/2		