DATA SHEET



Three Phase Induction Motor - Squirrel Cage									
Customer	:								
Product line	: W22 Phase		ower High	Efficiency 1	Γhree-	Product cod	e :	12173261 02089EP3PCT286V2F1-\	Λ/
						Catalog # :		02089EP3PC1286V2F1-V	/V
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torqu Breakdown torque Insulation class Service factor Moment of inertia		: 284/67 : 20 HP : 4 : 60 Hz : 200 V : 57.3 A : 344 A : 6.0x(C : 21.2 A : 1765 r : 1.94 % : 59.5 ft : 190 % : 240 % : F : 1.15 : 5.85 so	(15 kW) Rode G) pm		Temp Duty Ambi Altitu Prote Cooli Mour Rotat Noise Starti	ent temperaturede ction degree ng method otting	re	: 25s (cold) 14s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-1 : Both (CW and CCW) : 64.0 dB(A) : Direct On Line : 471 lb	
Output	25%	50%	75%	100%	Founda	ation loads			
Efficiency (%) Power Factor	87.5 67.7 0.46 0.20				Max. tra	action ompression		: 77 lb : 547 lb	
Bearing type Sealing Lubrication interva Lubricant amount Lubricant type	ıl	: : : : : : : : : : : : : : : : : : : :	<u>Drive 6</u> 6311 2F V'Ri - -	RS C3	bil Polyre	Non driv 6211 2 V'R - ex EM	RS C3		
Notes:									

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

DATA SHEET

	П
	ш

Three Phase Induction Motor - Squirrel Cage						
Customer	:					
Voltage: 110-127	7/200-240 V	Space heater informa	ation			
Voltage: 110-127	7200-240 V					
Rev.		Changes Summary	Performed	Checked	Date	
					_	
Performed by						
Checked by				Page	Revision	
Date	28/03/2024			2/2		