

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Cooling Tower NEMA Premium  
Efficiency Three-Phase

Product code : 12024061

Catalog # : 00518ET3HCT184T-W22

Frame : 182/4T  
Output : 5 HP (3.7 kW)  
Poles : 4  
Frequency : 60 Hz  
Rated voltage : 575 V  
Rated current : 5.19 A  
L. R. Amperes : 38.9 A  
LRC : 7.5x(Code J)  
No load current : 2.32 A  
Rated speed : 1750 rpm  
Slip : 2.78 %  
Rated torque : 15.0 ft.lb  
Locked rotor torque : 229 %  
Breakdown torque : 290 %  
Insulation class : F  
Service factor : 1.25  
Moment of inertia (J) : 0.4003 sq.ft.lb  
Design : B

Locked rotor time : 27s (cold) 15s (hot)  
Temperature rise : 80 K  
Duty cycle : Cont.(S1)  
Ambient temperature : -20°C to +40°C  
Altitude : 1000 m.a.s.l.  
Protection degree : IP55  
Cooling method : IC411 - TEFC  
Mounting : F-2  
Rotation<sup>1</sup> : Both (CW and CCW)  
Noise level<sup>2</sup> : 56.0 dB(A)  
Starting method : Direct On Line  
Approx. weight<sup>3</sup> : 99.1 lb

Output 25% 50% 75% 100%

Efficiency (%) 88.2 88.5 89.5 89.5  
Power Factor 0.38 0.62 0.74 0.80

Foundation loads

Max. traction : 228 lb  
Max. compression : 327 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
11.2	9.4	8.7	5.3	3.7	2.4	1.7

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type :		6207 2RS	6206 2RS
Sealing :		V'Ring	V'Ring
Lubrication interval :		-	-
Lubricant amount :		-	-
Lubricant type :		Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 2		
Checked by				
Date	28/03/2024			

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

### Space heater information

Voltage: 110-127/200-240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page		Revision
Checked by					
Date	28/03/2024				