

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 11458012

Catalog # : 00236ET3H145T-W22

Frame : 143/5T
Output : 2 HP (1.5 kW)
Poles : 2
Frequency : 60 Hz
Rated voltage : 575 V
Rated current : 2.15 A
L. R. Amperes : 19.2 A
LRC : 8.9x(Code L)
No load current : 0.960 A
Rated speed : 3500 rpm
Slip : 2.78 %
Rated torque : 3.00 ft.lb
Locked rotor torque : 270 %
Breakdown torque : 380 %
Insulation class : F
Service factor : 1.25
Moment of inertia (J) : 0.0605 sq.ft.lb
Design : B

Locked rotor time : 21s (cold) 12s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 68.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 49.4 lb

Output 25% 50% 75% 100%

Efficiency (%) 82.1 82.5 85.5 85.5
Power Factor 0.40 0.64 0.76 0.82

Foundation loads

Max. traction : 74 lb
Max. compression : 124 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
15.7	12.3	11.6	8.8	5.4	3.9	2.7

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6205 ZZ	6204 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	28/03/2024			

Page 1 / 1
Revision