DATA SHEET



Inree Phase Induction Motor - Squirrei Cage									
Customer	:								
Product line	: W22 Phase	•	ower High	Efficiency T	hree-	Product code :	121	172999	
	i ilast	•				Catalog # :	007 W	789EP3QCT254V2	2F1-
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Breakdown torque Insulation class Service factor Moment of inertia (a		: 254T : 7.5 HF : 4 : 60 Hz : 460 V : 9.30 A : 79.1 A : 8.5x(C : 3.55 A : 1780 I : 1.11 % : 22.1 ff : 260 % : 360 % : F : 1.15 : 2.62 s	Code K) Copm Commons		Tempe Duty of Ambie Altitud Protec Coolin Mount Rotati Noise Startir	nt temperature e tiion degree g method ing on ¹	: 8 : C : -2 : 1 : IF : IG : F : B : 6	2s (cold) 18s (hot) 0 K Cont.(S1) 20°C to +40°C 000 m.a.s.l. 255 C411 - TEFC -1 soth (CW and CCV 4.0 dB(A) Direct On Line 90 lb	
Output	25%	50%	75%	100%	Foundat	ion loads			
Efficiency (%)	84.9 69.0	85.5 71.0	88.2 77.0	88.5 79.0	Max. tra	ction	: 28	lb	
, ,		0.68 0.37			Max. co	mpression	: 318	3 lb	
Bearing type		:	Drive 6 6309 21	RS C3		Non drive end 6209 2RS C	_		

V'Ring Lubrication interval

Lubricant amount Lubricant type Mobil Polyrex EM

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

DATA SHEET

	П
	ш

Three Phase Induction Motor - Squirrel Cage						
Customer	:					
Voltage: 110-127	7/200-240 V	Space heater informa	ation			
Voltage: 110-127	7200-240 V					
Rev.		Changes Summary	Performed	Checked	Date	
					_	
Performed by						
Checked by				Page	Revision	
Date	28/03/2024			2/2		