

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Cooling Tower High Efficiency Three-Phase

Product code : 12180340

Catalog # : 07589EP3QCT404VF1-W2

Frame : 404/5T
 Output : 75 HP (55 kW)
 Poles : 4
 Frequency : 60 Hz
 Rated voltage : 460 V
 Rated current : 85.3 A
 L. R. Amperes : 682 A
 LRC : 8.0x(Code J)
 No load current : 32.0 A
 Rated speed : 1780 rpm
 Slip : 1.11 %
 Rated torque : 221 ft.lb
 Locked rotor torque : 240 %
 Breakdown torque : 280 %
 Insulation class : F
 Service factor : 1.15
 Moment of inertia (J) : 27.4 sq.ft.lb

Locked rotor time : 14s (cold) 8s (hot)
 Temperature rise : 80 K
 Duty cycle : Cont.(S1)
 Ambient temperature : -20°C to +40°C
 Altitude : 1000 m.a.s.l.
 Protection degree : IP55
 Cooling method : IC411 - TEFC
 Mounting : F-1
 Rotation¹ : Both (CW and CCW)
 Noise level² : 71.0 dB(A)
 Starting method : Direct On Line
 Approx. weight³ : 1176 lb

Output	25%	50%	75%	100%				
Efficiency (%)	91.0	87.7	91.7	88.5	92.4	89.5	93.0	90.2
Power Factor	0.47	0.26	0.74	0.45	0.82	0.57	0.87	0.64

Foundation loads
 Max. traction : 5 lb
 Max. compression : 1180 lb

	Drive end	Non drive end
Bearing type	6316 2RS C3	6314 2RS C3
Sealing	WSeal	WSeal
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	POLYREA ESTER OIL (WT/ ENS)	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2 Revision		
Checked by				
Date	28/03/2024			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Space heater information

Voltage: 110-127/200-240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page		Revision
Checked by					
Date	28/03/2024				