## **DATA SHEET**



Three Phase	e Indud	ction M	otor - S	Squirrel	Cage		<u>ШЕ</u>	Ц
Customer	:							
Product line		: W22 Cooling Tower High Efficiency T Phase				Product code :	12174933	
						Catalog # :	04089EP3QCT364V2F1- W	
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Breakdown torque Insulation class Service factor Moment of inertia	•	: 4 : 60 Hz : 460 V : 46.8 A : 337 A	Code H)		Temp Duty ( Ambie Altitud Prote Coolin Moun Rotat Noise Startii	ent temperature de ction degree ng method ting	: 14s (cold) 8s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-1 : Both (CW and CCW) : 71.0 dB(A) : Direct On Line : 858 lb	
Output	25%	50%	75%	100%	Founda	tion loads		
Efficiency (%) Power Factor				92.4 81.5 0.87 0.64	Max. tra Max. co	action ompression	: 78 lb : 936 lb	
Bearing type Sealing Lubrication interva Lubricant amount	al	: : : : : : : : : : : : : : : : : : : :	<u>Drive</u> 6314 2 WS			Non drive end 6314 2RS C3 WSeal - -		
Lubricant type : POLYREA E				ESTER C	IL (WT/ ENS)			

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

## DATA SHEET

		П
Ш		Ц

Three Pha	se Induction	<u> </u>			
Customer	:				
		Space heater info	rmation		
Voltage: 110-127	7/200-240 V	Space neater info	mation		
Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision

2/2

28/03/2024

Date