## DATA SHEET



Three Phase Induction Motor - Squirrel Cage								
Customer	:							
Product line		: W22 Cooling Tower High Efficiency T Phase				Product code :	12173349	
						Catalog # :	02089EP3QCT286V2F1- W	
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Insulation class Service factor		: 284/6 <sup>-</sup> : 20 HP : 4 : 60 Hz : 460 V : 24.9 A : 149 A : 6.0x(C : 9.20 A : 1765 r : 1.94 % : 59.5 ft : 190 % : 240 %	code G) cpm 6		Temp Duty of Ambie Altitud Prote Coolin Moun Rotat Noise Startin	ent temperature de ction degree ng method ting	: 25s (cold) 14s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-1 : Both (CW and CCW) : 64.0 dB(A) : Direct On Line : 470 lb	
Moment of inertia		: 5.85 s	<u> </u>	1000/				_
Output	25%	50%	75%	100%	Founda Max. tra	tion loads	: 77 lb	
Efficiency (%) Power Factor		88.5 70.0 0.71 0.35				empression	: 77 lb : 547 lb	
Bearing type Sealing Lubrication interva	ı	:	<u>Drive 6</u> 6311 2F V'Ri	RS C3		Non drive end 6211 2RS C3 V'Ring		
Lubricant amount	•	:	-			-		

Mobil Polyrex EM

Notes:

Lubricant type

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

## DATA SHEET

		П
Ш		Ц

Three Phase Induction Motor - Squirrel Cage				<u> </u>		
Customer	:					
		Space heater info	rmation			
Voltage: 110-127	7/200-240 V	Space neater info	mation			
Rev.		Changes Summary	Performed	Checked	Date	
Performed by						
Checked by				Page	Revision	

2/2

28/03/2024

Date