## **DATA SHEET**

## Three Phase Induction Motor - Squirrel Cage



This of the control o							
Customer	:						
Product line	: W22 Phase	•	ower High	Efficiency T	hree-	Product code : Catalog # :	12172473 00389EP3QCT182V-W22
						Catalog # .	00309EF3QC1102V-W22
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Insulation class Service factor Moment of inertia	)	: 4 : 60 Hz : 460 V : 3.99 A : 29.9 A : 7.5x(C : 2.30 A : 1755 r : 2.50 % : 8.98 ft : 200 % : 290 % : F : 1.15	code J) pm		Temp Duty ( Ambie Altitud Prote Coolin Moun Rotat Noise Startin	ent temperature de ction degree ng method ting	: 18s (cold) 10s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-2 : Both (CW and CCW) : 58.0 dB(A) : Direct On Line : 91.2 lb
Output	25%	50%	75%	100%	Founda	tion loads	
Efficiency (%)	79.5 64.3	81.5 65.0	85.5 72.0	87.5 72.0	Max. tra	action	: 17 lb
Power Factor	0.34 0.20	0.58 0.40	0.70 0.48	0.79 0.55	Max. co	ompression	: 108 lb
Bearing type Sealing Lubrication interva	al	: : :	Drive 6 6207 V'Ri	2RS		Non drive end 6206 2RS V'Ring -	

Mobil Polyrex EM

Notes:

Lubricant amount Lubricant type

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

## DATA SHEET

		П
Ш		Ц

Three Pha	se Induction	<u> </u>			
Customer	:				
		Space heater info	rmation		
Voltage: 110-127	7/200-240 V	Space neater info	mation		
Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision

2/2

28/03/2024

Date