

# DATA SHEET



## Three Phase Induction Motor - Squirrel Cage

Customer :				
Product line : W40 NEMA Premium Efficiency Three-Phase		Product code : 14285047		
		Catalog # : 075180T3ERB365T-W40		
Frame	: 364/5T	Locked rotor time	: 25s (cold) 14s (hot)	
Output	: 75 HP (55 kW)	Temperature rise	: 80 K	
Poles	: 4	Duty cycle	: Cont.(S1)	
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C	
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.	
Rated current	: 171/85.5 A	Protection degree	: IP23	
L. R. Amperes	: 1163/581 A	Cooling method	: IC01 - ODP	
LRC	: 6.8x(Code G)	Mounting	: F-1	
No load current	: 61.0/30.5 A	Rotation <sup>1</sup>	: Both (CW and CCW)	
Rated speed	: 1780 rpm	Noise level <sup>2</sup>	: 69.0 dB(A)	
Slip	: 1.11 %	Starting method	: Direct On Line	
Rated torque	: 221 ft.lb	Approx. weight <sup>3</sup>	: 799 lb	
Locked rotor torque	: 220 %			
Breakdown torque	: 260 %			
Insulation class	: F			
Service factor	: 1.25			
Moment of inertia (J)	: 16.8 sq.ft.lb			
Design	: B			
Output	25%	50%	75%	100%
Efficiency (%)	94.4	93.7	94.5	93.8
	95.0	94.2	95.0	94.2
	93.7	93.7	93.8	93.8
	94.2	94.2	94.2	94.2
Power Factor	0.48	0.48	0.73	0.73
	0.82	0.82	0.85	0.86
	0.43	0.40	0.69	0.66
	0.80	0.77	0.84	0.83
Foundation loads		Max. traction : 1638 lb		
		Max. compression : 2437 lb		
Bearing type	:	<u>Drive end</u>	<u>Non drive end</u>	
Sealing	:	NU-314 C3	6314 C3	
Lubrication interval	:	Without Bearing Seal	Without Bearing Seal	
Lubricant amount	:	20000 h	20000 h	
Lubricant type	:	27 g	27 g	
		Mobil Polyrex EM		
Notes:				
This revision replaces and cancel the previous one, which must be eliminated.		These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
(1) Looking the motor from the shaft end.				
(2) Measured at 1m and with tolerance of +3dB(A).				
(3) Approximate weight subject to changes after manufacturing process.				
(4) At 100% of full load.				
Rev.	Changes Summary		Performed	Checked
Performed by				
Checked by				
Date	28/03/2024		Page	Revision
			1 / 1	