## **DATA SHEET**



Inree Phase	e inaud	ction ivid	otor - S	quirrei	Cage				
Customer	:								
Product line		: W22 Cooling Tower High Efficiency T				Three- Product code :		19083	
						Catalog # :	005 W2	26EP3QCT254VF	<del>-</del> 1-
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torqu Breakdown torque Insulation class Service factor Moment of inertia	9	: 254/6 : 1.25 H : 12 : 60 Hz : 460 V : 2.78 A : 9.17 A : 3.3x(C : 2.30 A : 587 rp : 2.17 % : 11.2 ft : 160 % : 240 % : F : 1.15 : 3.92 s	IP (0.92 kV Code G) cm 6	<b>V</b> )	Temp Duty Ambi Altitu Prote Cooli Mour Rota Noise Starti	ection degree ng method nting	: 80 : -2 : 10 : IF : IC : B: : 5	ont.(S1) 20°C to +40°C 000 m.a.s.l. 255 C411 - TEFC	
Output	25%	50%	75%	100%	Founda	ation loads			
Efficiency (%)		73.0 86.5			Max. tr		: 239		
Power Factor	0.18 0.31	0.34 0.55	0.44 0.68	0.52 0.76	Max. co	ompression	: 504	. lb	
Bearing type Sealing Lubrication interva	al	:	<u>Drive 6</u> 6309 2 V'R	RS C3	,	Non drive o 6209 2RS V'Ring	S C3		
Lubricant amount		:	-			-			
Lubricant type		:		Mo	bil Polyre	ex EM			

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

## DATA SHEET

		П
Ш		Ц

Three Pha	se Induction	<u> </u>			
Customer	:				
		Space heater info	rmation		
Voltage: 110-127	7/200-240 V	Space neater info	mation		
Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision

2/2

28/03/2024

Date