DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Three i hase induction wotor - Squirrer Cage								
Customer	:							
Product line	: W22 Phase	•	ower High	Efficiency T	hree-	Product code : Catalog # :	12172967 00789EP3	PCT213V-W22
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Insulation class Service factor Moment of inertia	9	: 213T : 7.5 HF : 4 : 60 Hz : 200 V : 21.9 A : 184 A : 8.4x(C : 10.4 A : 1770 r : 1.67 % : 22.3 ft : 200 % : 300 % : F : 1.15 : 1.38 s	code K) pm 6		Temp Duty Ambi Altitude Prote Cooli Moun Rotat Noise Starti	ent temperature de ction degree ng method tting	: 80 K : Cont.(S' : -20°C to : 1000 m. : IP55 : IC411 -	+40°C a.s.l. TEFC W and CCW)
Output Efficiency (%) Power Factor		50% 85.5 74.0 0.64 0.40			Max. tra	ntion loads action ompression	: 128 lb : 130 lb	
Bearing type Sealing Lubrication interva		:	<u>Drive 6</u> 6308 V'Ri -	2RS		Non drive end 6207 2RS V'Ring - -	<u>I</u>	

Mobil Polyrex EM

Notes:

Lubricant type

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

DATA SHEET

	П
	ш

Three Pha	se Inductio	n Motor - Squirrel Cage			
Customer	:				
Voltage: 110-127	7/200-240 V	Space heater informa	ation		
Voltage: 110-127	7200-240 V				
Rev.		Changes Summary	Performed	Checked	Date
					_
Performed by					
Checked by				Page	Revision
Date	28/03/2024			2/2	