## **DATA SHEET**



Three Phase Induction Motor - Squirrel Cage									
Customer	:								
Product line	: W22 Phase		ower High	Efficiency 1	「hree-	Product code Catalog #:	:	12174040 03089EP3PCT324VF1	-W2
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Breakdown torque Insulation class Service factor Moment of inertia	•	: 324T : 30 HP : 4 : 60 Hz : 200 V : 85.5 A : 693 A : 8.1x(C : 39.1 A : 1780 r : 1.11 % : 88.5 ff : 270 % : 280 % : F : 1.15 : 7.85 s	Code J)		Temp Duty Ambi Altitu Prote Cooli Mour Rota Noise Starti	ection degree ng method nting		: 19s (cold) 11s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-1 : Both (CW and CCW) : 69.0 dB(A) : Direct On Line : 542 lb	)
Output Efficiency (%) Power Factor	89.4 81.0			91.7 85.5 0.81 0.57	Max. tr	ation loads action ompression		: 19 lb : 561 lb	
Bearing type Sealing Lubrication interva Lubricant amount Lubricant type	al	: : : : : : : : : : : : : : : : : : : :	<u>Drive</u> 6312 2 V'R - -	RS C3 ing	bil Polyre	Non drive 6212 2R V'Rir - - ex EM	RS C3		
Notes:									

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

## DATA SHEET

		П
Ш		Ц

Three Pha	se Induction	<u> </u>			
Customer	:				
		Space heater info	rmation		
Voltage: 110-127	7/200-240 V	Space neater info	mation		
Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision

2/2

28/03/2024

Date