## **DATA SHEET**



Three Phase Induction Motor - Squirrel Cage							
Customer	:						
Product line	: W2: Phas	2 Cooling T	ower High	Efficiency T	<sup>-</sup> hree-	Product code : Catalog # :	12172970 00789EP3PCT254V2-W22
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Breakdown torque Insulation class Service factor Moment of inertia	•	: 254T : 7.5 HF : 4 : 60 Hz : 200 V : 21.4 A : 182 A : 8.5x(C : 8.17 A : 1780 I : 1.11 % : 22.1 ff : 260 % : 360 % : F : 1.15 : 2.62 s	Code K) Crpm		Temp Duty Ambi Altitu Prote Cooli Mour Rotat Noise Starti	ent temperature de oction degree ng method tting	: 32s (cold) 18s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-2 : Both (CW and CCW) : 64.0 dB(A) : Direct On Line : 290 lb
Output  Efficiency (%)  Power Factor		50% 0 85.5 71.0 1 0.68 0.37			Max. tra	ation loads action ompression	: 28 lb : 318 lb
Bearing type Sealing Lubrication interva Lubricant amount	al	: : :	<u>Drive 6</u> 6309 2F V'Ri -	RS C3		Non drive end 6209 2RS C3 V'Ring	

Mobil Polyrex EM

Notes:

Lubricant type

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

## DATA SHEET

	П
	ш

Three Pha	se Inductio	n Motor - Squirrel Cage			
Customer	:				
Voltage: 110-127	7/200-240 V	Space heater informa	ation		
Voltage: 110-127	7200-240 V				
Rev.		Changes Summary	Performed	Checked	Date
					_
Performed by					
Checked by				Page	Revision
Date	28/03/2024			2/2	