

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 Cooling Tower NEMA Premium Efficiency Three-Phase Product code : 12095888
 Catalog # : 07518ET3PCT365T-W22

Frame	: 364/5T	Locked rotor time	: 25s (cold) 14s (hot)
Output	: 75 HP (55 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 200 V	Altitude	: 1000 m.a.s.l.
Rated current	: 201 A	Protection degree	: IP55
L. R. Amperes	: 1284 A	Cooling method	: IC411 - TEFC
LRC	: 6.4x(Code G)	Mounting	: F-2
No load current	: 75.9 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1780 rpm	Noise level ²	: 67.0 dB(A)
Slip	: 1.11 %	Starting method	: Direct On Line
Rated torque	: 221 ft.lb	Approx. weight ³	: 0.0 lb
Locked rotor torque	: 240 %		
Breakdown torque	: 260 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 23.3 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	94.0	94.5	95.0	95.4	Max. traction	: 1969 lb
Power Factor	0.44	0.68	0.78	0.83	Max. compression	: 1969 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
4.7	3.8	3.5	2.4	1.6	1.1	0.7

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6314 2RS C3	6314 2RS C3
Sealing	:	WSeal	WSeal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	POLYREA ESTER OIL (WT/ ENS)	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.


- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	28/03/2024		1 / 2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Space heater information

Voltage: 110-127/200-240 V

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	28/03/2024		2 / 2	