

# DATA SHEET



## Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase  
 Product code : 14153912  
 Catalog # : 00512ET3H215TC-W22

Frame	: 213/5TC	Locked rotor time	: 102s (cold) 57s (hot)
Output	: 5 HP (3.7 kW)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 5.46 A	Protection degree	: IP55
L. R. Amperes	: 37.2 A	Cooling method	: IC411 - TEFC
LRC	: 6.8x(Code J)	Mounting	: F-1
No load current	: 2.76 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 1170 rpm	Noise level <sup>2</sup>	: 55.0 dB(A)
Slip	: 2.50 %	Starting method	: Direct On Line
Rated torque	: 22.4 ft.lb	Approx. weight <sup>3</sup>	: 177 lb
Locked rotor torque	: 170 %		
Breakdown torque	: 260 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 1.47 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	88.2	88.5	89.5	89.5	Max. traction	: 240 lb
Power Factor	0.34	0.58	0.70	0.76	Max. compression	: 418 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
11.1	9.1	8.8	5.8	4.0	2.9	2.1

	Drive end	Non drive end
Bearing type	: 6308 ZZ	: 6207 ZZ
Sealing	: V'Ring	: V'Ring
Lubrication interval	: -	: -
Lubricant amount	: -	: -
Lubricant type	: Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	29/03/2024		1 / 1	