

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency
Three-Phase

Product code : 11432185

Catalog # : 25036ST3QIE449TS-W22

Frame : 447/9TS
Output : 250 HP (185 kW)
Poles : 2
Frequency : 60 Hz
Rated voltage : 460 V
Rated current : 269 A
L. R. Amperes : 1802 A
LRC : 6.7x(Code G)
No load current : 62.0 A
Rated speed : 3573 rpm
Slip : 0.75 %
Rated torque : 367 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 240 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 50.3 sq.ft.lb
Design : B

Locked rotor time : 32s (cold) 18s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP56
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 81.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 2532 lb

Output	25%		50%		75%		100%	
Efficiency (%)	95.3	94.9	95.4	95.0	95.8	95.6	95.8	95.6
	95.0	95.0	95.1	95.1	95.6	95.6	95.6	95.6
	95.8	95.7	95.4	95.4	95.0	95.4	94.5	95.0
	95.6	95.4	95.8	95.8	95.8	95.8	95.4	95.4
Power Factor	0.62	0.62	0.84	0.84	0.89	0.89	0.90	0.90
	0.58	0.55	0.82	0.80	0.88	0.87	0.90	0.89
	0.67	0.64	0.87	0.85	0.90	0.89	0.90	0.90
	0.61	0.61	0.84	0.84	0.89	0.89	0.90	0.90

Foundation loads
Max. traction : 1444 lb
Max. compression : 3976 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	4.8	4.8	4.8	4.8	4.8	4.8	4.8
	P2 (0,5;1,0)	3.6	3.6	3.6	3.6	3.6	3.6	3.6
	P3 (0,25;1,0)	3.0	3.0	3.0	3.0	3.0	3.0	3.0
	P4 (0,9;0,5)	2.8	2.8	2.8	2.8	2.8	2.8	2.8
	P5 (0,5;0,5)	1.7	1.7	1.7	1.7	1.7	1.7	1.7
	P6 (0,5;0,25)	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	P7 (0,25;0,25)	0.7	0.7	0.7	0.7	0.7	0.7	0.7

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6314 C3	6314 C3
Sealing	:	Inpro/Seal	Inpro/Seal
Lubrication interval	:	4000 h	4000 h
Lubricant amount	:	27 g	27 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	25/03/2024			

Page 1 / 1
Revision