DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer Product line : W22 NEMA Premium Efficiency Three-Product code: 13827809 Catalog #: 45018ET3GKD586/7-W22 Frame : 586/7T Locked rotor time : 45s (cold) 25s (hot) Output : 450 HP (330 kW) Temperature rise : 80 K Poles Duty cycle : Cont.(S1) : -20°C to +40°C Frequency : 60 Hz Ambient temperature Rated voltage : 460 V : 1000 m.a.s.l. Altitude Rated current : 501 A Protection degree : IP55 L. R. Amperes : 3758 A Cooling method : IC411 - TEFC LRC : 7.5x(Code H) Mounting : F-1 No load current : 160 A Rotation¹ : Both (CW and CCW) Rated speed : 1786 rpm Noise level² : 78.0 dB(A) Starting method Slip : 0.78 % : Direct On Line Rated torque : 1320 ft.lb Approx. weight³ : 3912 lb Locked rotor torque : 240 % Breakdown torque : 250 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 229 sq.ft.lb Design 25% 50% 75% 100% Output Foundation loads 0.000 96.2 Efficiency (%) 95.8 96.2 Max. traction : 4945 lb Power Factor 0.00 0.86 0.75 0.83 Max. compression : 8857 lb Drive end Non drive end Bearing type NU-322 C3 6319 C3 Sealing Taconite Labyrinth Taconite Labyrinth Lubrication interval 4000 h 8000 h Lubricant amount 60 g 45 g Lubricant type Mobil Polyrex EM

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			1/2	

DATA SHEET

	П
Ш	Ш

Three Pha	se Induction	<u> </u>			
Customer	:				
Voltage: 200 - 24	10 V	Space heater infor	mation		
Rev.		Changes Summary	Performed	Checked	Date
Dorformadhi		I			
Performed by Checked by				Page	Revision

2/2

27/03/2024

Date