# **DATA SHEET**

### Three Phase Induction Motor - Squirrel Cage



: 72s (cold) 40s (hot)

: 80 K

: IP55

: F-1

: 114 lb

: Cont.(S1)

: -20°C to +40°C

: 1000 m.a.s.l.

: IC411 - TEFC

: 50.0 dB(A)

: Direct On Line

: Both (CW and CCW)

Customer

Product line : W21 Explosion Proof High Efficiency Three-Product code: 10083415

Locked rotor time

Temperature rise

Protection degree

Cooling method

Starting method

Approx. weight<sup>3</sup>

Non drive end

6206 2RS Lip Seal

Ambient temperature

Duty cycle

Altitude

Mounting

Rotation<sup>1</sup>

Noise level<sup>2</sup>

: 182T Frame

Output : 1 HP (0.75 kW)

Poles : 8 Frequency : 60 Hz : 230/460 V Rated voltage Rated current : 4.63/2.31 A L. R. Amperes : 27.8/13.9 A

**LRC** : 6.0x(Code M) No load current : 4.13/2.06 A

Rated speed : 875 rpm Slip : 2.78 % Rated torque : 6.00 ft.lb Locked rotor torque : 300 %

Breakdown torque : 350 % : F Insulation class Service factor : 1.15 Moment of inertia (J) : 0.3991 sq.ft.lb

Design

25% 50% 75% 100% Output Foundation loads

: 77 lb Efficiency (%) 66.1 68.0 72.0 74.0 Max. traction Power Factor 0.18 0.35 0.45 0.55 Max. compression : 191 lb

Drive end 6307 2RS Bearing type Oil Seal Sealing

Lubrication interval Lubricant amount

Lubricant type Mobil Polyrex EM

USABLE @208V 5.12A SF 1.15 SFA 5.88A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date	
Performed by						
Checked by					Page	Revision
Date	27/03/2024				1/2	

# DATA SHEET

# Three Phase Induction Motor - Squirrel Cage



_	
Customer	
Custoffici	

#### Thermal protection

	·					
ID	Application	Туре	Quantity	Sensing Temperature		
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C		

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			2/2	