## **DATA SHEET**

#### Three Phase Induction Motor - Squirrel Cage



i i i i oo i i i ao	o inidad		J.(J.)	quiitoi	Ougo	
Customer	:					
Product line	: W21 Phase		Proof Higl	n Efficiency	Three- Product code :	10674523
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Insulation class Service factor Moment of inertia Design	е	: 8 : 50 Hz : 380 V : 33.0 A : 125 A	Code D)  om  6 Ib		Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³	: 45s (cold) 25s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-1 : Both (CW and CCW) : 56.0 dB(A) : Direct On Line : 608 lb
Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)		86.5 87.5			Max. traction	: 704 lb
Power Factor	0.42 0.33	0.66 0.56	0.75 0.68	0.79 0.75	Max. compression	: 1312 lb
Bearing type Sealing	al	:	<u>Drive 6</u> 6312 2I Oil S	RS C3	Non drive end 6212 2RS C3 Lip Seal	

Mobil Polyrex EM

Notes:

Lubricant amount Lubricant type

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			1/2	

MG-1.

# DATA SHEET

### Three Phase Induction Motor - Squirrel Cage



_	
Customer	
Custoffici	

#### Thermal protection

		•		
ID	Application	Туре	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			2/2	